

Power Double Lock

TE Internal #: 1-2323832-1

Tin (Sn), Socket Contact, 20 – 18 AWG, 300 VAC, Crimp, Copper Alloy, Power, -30 – 150 °C [-22 – 302 °F], Power Double Lock

[View on TE.com >](#)



Connectors > Contacts > Connector Contacts



Contact Type: **Socket**
Contact Mating Area Plating Material: **Tin (Sn)**
Wire Contact Termination Area Plating Material: **Pre-Tin**
Operating Voltage: **300 VAC**
Contact Retention Within Housing: **With**

Features

Product Type Features

Discrete Wire Type	Stranded
Sealable	No

Electrical Characteristics

Operating Voltage	300 VAC
-------------------	---------

Contact Features

Contact Type	Socket
Contact Mating Area Plating Material	Tin (Sn)
Wire Contact Termination Area Plating Material	Pre-Tin
Contact Retention Within Housing	With
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	8 A
Wire Contact Termination Area Plating Thickness	.8 µm[31.49 µin]
Contact Orientation	Straight

Termination Features

--	--



Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Wire Size	20 – 18 AWG
Compatible Insulation Diameter Range	1.75 – 2.5 mm[.069 – .098 in]

Usage Conditions

Operating Temperature Range	-30 – 150 °C[-22 – 302 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Packaging Features

Packaging Quantity	4000
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Also in the Series

Power Double Lock

Connector Contacts(24)

Connector Hardware(13)

Power Contacts(24)

Rectangular Connector Housings(232)

Rectangular Power Connectors(275)

Standard Rectangular Connectors(232)

Wire-to-Board Connector Assemblies & Housings(33)

Documents

Product Drawings

PDL REC TERMINAL 18-20 AWG w/lube

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2323832-1_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2323832-1_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2323832-1_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

1-2323832-1

Tin (Sn), Socket Contact, 20 – 18 AWG, 300 VAC, Crimp, Copper Alloy, Power, -30 – 150 °C [-22 – 302 °F], Power Double Lock



Application Specification

English