

CII | CII HS Relay

TE Internal #: 2-1617108-4

General Purpose Signal Relay, DC, Non-Polarized, Monostable, 2 Form C DPDT-CO, 1 A Contact Rating, 5 VDC Coil Voltage, .25 W

Coil Power, CII HS Relay

View on TE.com >



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: General Purpose Signal Relay

Coil Magnetic System: Non-Polarized, Monostable

Contact Arrangement: 2 Form C DPDT-CO

Current Type: DC

Contact Current Rating: 1A

Features

Product Type Features

Product Type reatures	
Relay & Contactor Type	General Purpose Signal Relay
Configuration Features	
Contact Arrangement	2 Form C DPDT-CO
Electrical Characteristics	
Coil Resistance	100 Ω
Contact Switching Voltage (Max)	28 VDC
Contact Current Rating	1 A
Coil Voltage Rating	5 VDC
Coil Power Rating DC	.25 W
Body Features	
Enclosure Type	Hermetically Sealed
Termination Features	

Main Termination & Connection Type	Extended Leads
Coil Termination & Connection Type	Extended Leads

Mechanical Attachment

Product Mount Type	Board Mount	
--------------------	-------------	--

Usage Conditions



Operating Temperature Range	-55 – 85 °C
Environmental Ambient Temperature (Max)	85 °C[185 °F]
Operation/Application	
Vibration Resistance	10G's, 10 – 500Hz
Shock Resistance	30G's, 6ms
Coil Magnetic System	Non-Polarized, Monostable
Current Type	DC
Other	
Contact Current Class	≤2 A
Coil Power Rating Class	>.2 - ≤.3 W

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量超出标准 Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.



Compatible Parts



Also in the Series | CII HS Relay





Customers Also Bought























Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1617108-4_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1617108-4_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1617108-4_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

5-1773450-5_sec1_HM

English

RELAY

English