TE Internal #: 282618-1

Tin (Sn), Pin Contact, 26 – 22 AWG, .12 – .4 mm<sup>2</sup> Wire, Discrete

Wire, Insulation Displacement (IDC), Phosphor Bronze, Signal

View on TE.com >



Connectors > Contacts > Connector Contacts > 2.54mm FFC Connectors Pin Contacts



Contact Type: Pin

Contact Mating Area Plating Material: Tin (Sn)

Compatible With Wire & Cable Type: Discrete Wire

Wire Size: .12 – .4 mm<sup>2</sup>

All 2.54mm FFC Connectors Pin Contacts (33)

## **Features**

### **Configuration Features**

Compatible With Wire & Cable Type	Discrete Wire
Contact Features	
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	1 – 3 μm
Contact Mating Area Plating Material Finish	Matte
Contact Type	Pin
Contact Mating Area Plating Material	Tin (Sn)
Contact Base Material	Phosphor Bronze
Termination Features	
Termination Method to Wire & Cable	Insulation Displacement (IDC)
Product Terminates To	Wire & Cable
Dimensions	
Accepts Conductor Width	2.33 mm



Compatible Insulation Diameter Range	1.02 – 1.42 mm[.04 – .056 in]
Wire Size	.12 – .4 mm²
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Method	Reel

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts












# Customers Also Bought












TE Part #280365

AMPMODU, DBL ROW, CONTACT
REC











### **Documents**

Product Drawings
FFC PIN CONTACT TIN-P

English

#### **CAD Files**

Customer View Model ENG\_CVM\_CVM\_282618-1\_B.2d\_dxf.zip

English

3D PDF

Tin (Sn), Pin Contact, 26 – 22 AWG, .12 – .4 mm<sup>2</sup> Wire, Discrete Wire, Insulation Displacement (IDC), Phosphor Bronze, Signal



3D

**Customer View Model** 

ENG\_CVM\_CVM\_282618-1\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_282618-1\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.