

Manual motor controller, Easy TeSys GP2E, 3P,6-10A, thermal magnetic trip, screw clamp terminals

GP2E14

Main

Range	Easy TeSys
Product name	Easy TeSys GP2E
Product or component type	Motor controller
Device short name	GP2E
Device application	Motor
Trip unit technology	Thermal-magnetic

Complementary

Complementary	
Poles description	3P
Network type	AC
Utilisation category	AC-3 IEC 60947-4-1 Category A IEC 60947-2
Network frequency	50/60 Hz IEC 60947-4-1
Fixing mode	35 mm symmetrical DIN rail clipped Panel screwed with adaptor plate)
Operating position	Any position
Breaking capacity	100 kA Icu 230/240 V AC 50/60 Hz IEC 60947-2 100 kA Icu 400/415 V AC 50/60 Hz IEC 60947-2 15 kA Icu 440 V AC 50/60 Hz IEC 60947-2 10 kA Icu 500 V AC 50/60 Hz IEC 60947-2 3 kA Icu 690 V AC 50/60 Hz IEC 60947-2
[lcs] rated service short-circuit breaking capacity	100 % 230/240 V AC 50/60 Hz IEC 60947-2 100 % 400/415 V AC 50/60 Hz IEC 60947-2 100 % 440 V AC 50/60 Hz IEC 60947-2 100 % 500 V AC 50/60 Hz IEC 60947-2 75 % 690 V AC IEC 60947-2
Control type	Push-button
[In] rated current	10 A
thermal protection adjustment range	610 A
Magnetic tripping current	138 A
[Ue] rated operational voltage	690 V AC 50/60 Hz IEC 60947-2
[Ui] rated insulation voltage	690 V AC 50/60 Hz IEC 60947-2
[Ith] conventional free air thermal current	10 A IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-2
Power dissipation per pole	2.5 W
Mechanical durability	100000 cycles

Electrical durability	100000 cycles AC-3 440 V	
maximum operating rate	25 cyc/h	
Rated duty	Continuous IEC 60947-4-1	
Connections - terminals	Screw clamp terminals 0.0020.009 in² (16 mm²) - solid Screw clamp terminals 0.0020.009 in² (1.56 mm²) - flexible without cable end Screw clamp terminals 0.0020.006 in² (14 mm²) - flexible with cable end Screw clamp terminals AWG 18AWG 8)	
Tightening torque	15.05 lbf.in (1.7 N.m) screw clamp terminals	
Suitability for isolation	Yes IEC 60947-1	
Phase failure sensitivity	Yes IEC 60947-4-1	
Height	3.5 in (89 mm)	
Width	1.8 in (45 mm)	
Depth	3.09 in (78.5 mm)	
Net weight	0.57 lb(US) (0.26 kg)	

Environment

Standards	EN/IEC 60947-2 EN/IEC 60947-4-1 UL 60947-4-1 CUL
Product certifications	cUL
Protective treatment	тн
IP degree of protection	IP20 IEC 60529
IK degree of protection	IK04
Ambient air temperature for operation	-4140 °F (-2060 °C)
Ambient air temperature for storage	-40176 °F (-4080 °C)
Fire resistance	1760 °F (960 °C) IEC 60695-2-1
Operating altitude	2000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.3 in (8.5 cm)
Package 1 Width	1.8 in (4.6 cm)
Package 1 Length	3.64 in (9.25 cm)
Package 1 Weight	0.644 lb(US) (0.292 kg)
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	5.9 in (15 cm)
Package 2 Width	11.8 in (30 cm)
Package 2 Length	15.7 in (40 cm)
Package 2 Weight	15.450 lb(US) (7.008 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	768

Package 3 Height	27.6 in (70 cm)	
Package 3 Width	31.5 in (80 cm)	
Package 3 Length	47.2 in (120 cm)	
Package 3 Weight	494.400 lb(US) (224.256 kg)	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	41	

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	04104e70-ba29-493c-b2cc-b5837d1f879b
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative







