



Rev	AWO #	Description	Date	Appr
-		RELEASED	4/1/05	

654321

APPROVED: _____

DATE: _____ TITLE: _____



SPECIFICATIONS:

Material:
Insulator: PBT, glass reinforced, rated UL 94V-0
Insulator color: Black
Contacts: Phosphor Bronze
Plating:
G = Gold flash over Nickel underplate overall
T = Tin over Copper underplate overall
Electrical:
Operating voltage: 250 VAC max
Current rating: 1 Amp max
Contact resistance: 20 mohms max
Insulation resistance: 5,000 Mohms min
Dielectric withstanding voltage: 1,000 VAC for 1 minute
Temperature Rating:
Operating temperature: -55°C to +105°C
Environmental:
Lead free, RoHS compliant

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE
.079 [2.00] MINI SHUNT, OPEN TOP
.177 [4.50] HEIGHT

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED INCHES HOLES .X ± .10 .XX ± .020 .XXX ± .015 ØX ± .10 ØXX ± .015 ØXXX ± .010			TITLE 909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710 .<079 [2.00] MINI SHUNT, OPEN TOP .177 [4.50] HEIGHT		
APPROVALS		DATE		SIZE	
DRAWN		SS		PART NO.	
CHECKED		4/1/05		MS2A-X	
APPROVED				REF: X	
				SCALE: NTS	
				SHEET 1 OF 1	
				REV: -	

A

B

C

D

A

B

C

D

6

5

4

3

2

1