

Power Divider, 3-way, 2-18GHz, SMA Female

WM3PD-2-18-S





Parameter	Low Band	Mid Band	High Band	Unit
Frequency Range	2000-8000	8000-12400	12400-18000	MHz
Impedance	50			Ω
Return Loss (Port S)	14	10	10	dB, min.
Return Loss (Port 1-2)	15	13	13	dB, min.
Insertion Loss above 4.78dB	0.9	1.4	1.9	dB, max.
Isolation	18	18	15	dB, min.
Amplitude Unbalance ($\pm$) ¹	0.6	0.8	1.0	dB, max.
Phase Unbalance ($\pm$) ¹	8	10	12	Degree, max.
Input Power (CW) ²	25			W, max.
Combining Power (CW) ²	0.09			W/port, max.
DC Current	0.2			A/port, max.



Connector Interface	SMA Female
Operating Temperature ³	-55 to +85 °C
Storage Temperature	-55 to +100 °C
Nominal Weight	200 g (7.0 oz)
Operating Humidity	10-90% (non-condensing)
Operating Environment	Indoor Use Only
HTSUS Code	8548.00.0000
ECCN	EAR99

RoHS Status ⁴	RoHS3 Compliant
REACH Status ⁴	REACH Unaffected
Enclosure Material	Aluminum
Connectors Material	Stainless Steel
Contacts Material	Beryllium Copper, Gold Plated
Insulators Material	Virgin PTFE
Finish	Green Paint
Country of Origin	United States of America



1. With reference to average.
2. All output ports should be terminated in a 50-ohm load with 1.2:1 max VSWR.
3. Electrical specifications are tested at +25 °C.
4. To the best of our knowledge at the time of publication.



Typical Performance at +25 °C







Typical Performance Over Temperature









Typical Performance Data

Frequency (MHz)	Return Loss (dB)			Total Loss (dB)		Isolation (dB)	
	Port S	Port 1	Port 3	S-1	S-3	1-2	1-3
2000	19.5	27.5	28.3	5.0	5.0	22.2	23.8
2500	21.7	20.0	19.1	5.0	5.0	23.7	24.9
3000	20.6	21.3	21.4	5.0	5.0	22.3	25.9
3500	29.6	27.1	26.0	5.0	5.0	25.4	27.1
4000	20.1	27.0	25.0	5.0	5.0	22.6	27.3
4500	19.5	30.9	30.8	5.1	5.1	22.8	27.5
5000	23.8	21.2	20.5	5.1	5.1	25.0	31.1
5500	19.7	29.3	33.4	5.1	5.1	22.3	36.5
6000	24.6	32.7	27.2	5.1	5.1	26.0	31.3
6500	17.2	27.0	24.1	5.2	5.2	23.9	27.6
7000	17.7	24.8	22.7	5.2	5.3	21.4	25.2
7500	28.2	24.4	25.7	5.1	5.2	28.1	29.9
8000	17.5	25.6	23.2	5.2	5.2	22.7	40.5
8500	24.5	32.4	26.0	5.2	5.2	26.0	53.1
9000	17.0	20.4	19.1	5.3	5.4	25.1	32.2
9500	15.6	20.8	24.2	5.4	5.4	22.1	29.1
10000	28.4	27.8	25.2	5.3	5.3	26.4	32.3
10500	17.8	22.7	20.5	5.4	5.4	24.6	33.2
11000	21.2	24.0	24.6	5.3	5.4	26.4	34.7
11500	17.3	19.7	21.8	5.5	5.5	25.7	47.0
12000	16.4	24.0	22.6	5.5	5.6	22.2	37.8
12500	21.4	21.2	21.1	5.4	5.4	27.0	41.9
13000	18.0	21.5	23.2	5.5	5.5	25.4	33.1
13500	26.9	26.5	27.6	5.5	5.5	28.3	32.9
14000	18.3	24.7	26.1	5.5	5.6	28.3	37.8
14500	15.9	22.0	21.7	5.6	5.6	24.3	33.7
15000	26.5	24.4	25.6	5.5	5.5	33.6	40.0
15500	14.0	17.6	18.6	5.7	5.8	26.7	33.0
16000	25.5	29.0	30.8	5.5	5.6	26.9	25.6
16500	22.1	25.5	24.2	5.6	5.7	30.6	25.3
17000	12.8	17.4	17.3	5.8	5.9	27.8	24.3
17500	23.8	19.0	18.4	5.6	5.7	23.9	28.1
18000	15.8	17.8	16.5	5.7	5.8	24.9	38.6

Simplified Electrical Schematic



Outline Dimensions



Outline drawing: OL-3182

Dimensions are in inches, [mm] shown for convenience.

Tolerances on 2-pl decimals: ± 0.03 . 3-pl decimals: ± 0.015 .

The information contained in this document is accurate to the best of our knowledge and representative of the product described herein at the date of publication. It may be necessary to make modifications to the product and/or documentation of the product. Werbel Microwave LLC reserves the right to make such changes as required without notice. Unless otherwise stated, all specifications and dimensions are nominal. Werbel Microwave LLC does not make any representation or warranty regarding the suitability of the product described herein for any particular purpose or application, and Werbel Microwave LLC does not assume any liability arising out of the use of any part of documentation. This document gives only a description of the product(s) and shall not form part of any contract. Please contact a Werbel Microwave LLC Applications Engineer for the most current specification drawing.

Reliability testing was performed as an internal requalification of the product to substantiate the published specifications, which were previously arrived at by calculation and/or similarity to existing products. The results of these tests are provided as a courtesy and shall not form part of a contract or warranty. While reliability tests may depict the product being tested beyond the published specification ratings for the purpose of stress testing the product, this does not imply that the product should be operating above the rated limits for any length of time. Specifications related to reliability (e.g., performance over temperature, power handling, DC current, HI-POT) are "designed to meet" and are not individually tested in production of commercially available products. Please contact a Werbel Microwave LLC Applications Engineer if specific reliability testing is needed on a particular product.