

SIGN	DATE	DESCRIPTION	APPROVER
△	02/13/06	Part No. is changed.	Seamus
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

Technical Data

◆ **Material:**
Pin (outer sleeve): Brass, machined, CuZn38Pb2
Clip(contact 4 finger): Beryllium copper, heat treated or PHBZ
Plating(outer sleeve): Tin plated: 2um/80u"nickel, 5um/200u"tin
Gold plated: 2um/80u"nickel, full gold
2um/80 u"nickel, gold or tin plating
Plating clip(contact):
Insulator body(black): Glass filled thermoplastic polyester UL94 V-0

◆ **Electrical**
Current rating: 3 Amps/contact max.
Contact resistance: $\leq 4m\Omega$ /contact
Insulation resistance: $\geq 10000M\Omega$ at 500VAC
Rated voltage: 100 VRMS /150VDC

◆ **Mechanical**
Operating temperature: Gold plated: -55℃ to +125℃
-67℉ to +105℉
Tin plated: -40℃ to +105℃

Average insertion force with steel pin of: $\phi 0.43mm/0.017"$ < 250g
Average withdrawal force with steel pin of $\phi 0.43mm/0.017"$ > 50g
Mechanical life: min.200

◆ Applications and features:

- 1.The open frame is most common type.
- 2.The open body design gives better access (for cleaning and inspections) to air -cooling.
- 3.Side and end stackable.
- 4.High retention design prevents IC walkout during heavy vibration.
- 5.Closed bottom sleeve for 100% anti-wicking of silder.
- 6.Twist free construction.

◆ Environmental data

Solderability (IEC 60068-2-20. Ta): 235℃, 2s
Resistance to soldering heat (IEC 60068-2-20. Tb):
-Through hole mount components: 260℃, 10s

SA - XX 0 0 X 0 XXXXG △


No. of contacts: 01 ~ 40


pin plated: Code	Clip plated	Pin plated		
0	Gold Flash	Tin 200u"	0000	Clip BeCu
1	Gold 10u"	Tin 200u"	5QH0	Clip 5210
2	Gold 30u"	Tin 200u"		
3	Tin 200u"	Tin 200u"		
4	Gold flash	Gold flash		
5	Gold 10u"	Gold flash		
6	Gold 30u"	Gold flash		

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		IC/SKT Single row 7.43mmL finished products series(ROHS)					
PART NO.	SAXX00X0XXXXG			DWG NO.	8SA0101		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance		
		Aaron 2006.01.12	Aaron 2006.01.12			X.	±0.50
						X.X	±0.30
						X.XX	±0.10
						X*	±1*
					SHEET: 01/01	REV.: C	



Contact	Dim A	Dim B	Contact	Dim A	Dim B	Contact	Dim A	Dim B
01	2.54		15	38.10	35.56	29	73.66	71.12
02	5.08	2.54	16	40.64	38.10	30	76.20	73.66
03	7.62	5.08	17	43.18	40.64	31	78.74	76.20
04	10.16	7.62	18	45.72	43.18	32	81.28	78.74
05	12.70	10.16	19	48.26	45.72	33	83.82	81.28
06	15.24	12.70	20	50.80	48.26	34	86.36	83.82
07	17.78	15.24	21	53.34	50.80	35	88.90	86.36
08	20.32	17.78	22	55.88	53.34	36	91.44	88.90
09	22.86	20.32	23	58.42	55.88	37	93.98	91.44
10	25.40	22.86	24	60.96	58.42	38	96.52	93.98
11	27.94	25.40	25	63.50	60.96	39	99.06	96.52
12	30.48	27.94	26	66.04	63.50	40	101.60	99.06
13	33.02	30.48	27	68.58	66.04			
14	35.56	33.02	28	71.12	68.58			