TE Internal #: 1747367-1

Board-to-Board, 5 Position, 2.5 mm [.098 in] Centerline, Receptacle,

30 VDC, Right Angle, Printed Circuit Board, Power & Signal, DC

Jack Connectors


View on TE.com >



Connectors > PCB Connectors > Battery Connectors & Holders > DC Jack Connectors











Connector System: Board-to-Board

Number of Positions: 5

Centerline (Pitch): 2.5 mm [.098 in]

Connector & Housing Type: Receptacle

Operating Voltage: 30 VDC

Features

Product Type Features

Troduct Type realures	
Connector System	Board-to-Board
Connector & Housing Type	Receptacle
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	5
PCB Mount Orientation	Right Angle
Electrical Characteristics	
Operating Voltage	30 VDC
Contact Features	
Contact Current Rating (Max)	7 A
Mechanical Attachment	
PCB Mount Retention	Without

Board Mount

Connector Mounting Type



Centerline (Pitch)	2.5 mm[.098 in]
Usage Conditions	
Operating Temperature Range	-20 - 80 °C[-4 - 176 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Tray
Packaging Quantity	110

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Reflow solder capable to 245°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # 1473971-2 REC ASS'Y V TYPE FOR 2.5MM PIT



TE Part # 1565986-2 REC ASSY,2.5 SLIM BATTERY CONN



TE Part # 1565986-1 REC ASSY,2.5 SLIM BATTERY CONN





TE Part # 6318790-1 PLUG ASSY,PB-FREE,2.5 SLIM BATTERY OFF-S



Customers Also Bought



TE Part #DRC20-60P06 HDR, 60P, BLK, ST, AU/NI/CU, 06



TE Part #803765-SF FN9222SR-6-06



TE Part #CONMHF4-SMD-G-T MHF4 Jack 50 Ohm PCB Surface Mount



TE Part #215460-6
MICRO-MATCH FEM.SE





TE Part #1612898-1 BATTERY BLOCK CONN. PLUG ASSY



TE Part #5-1625984-6 HSA50 3R3 5%



TE Part #1658614-2 25 POS HDF RCPT, AP, LEAD FREE



TE Part #1747786-1
PACKING,REC. ASSY. 8POS. 2MM
PITCH BATTE



Documents



Product Drawings

RECEPTACLE ASSEMBLY 2.5MM PITCH BATTERY

Japanese

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1747367-1_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1747367-1_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1747367-1_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

2.5mm Pitch Battery Connector

Japanese

Product Specification

Japanese