



Color coding acc. to DIN VDE 47100	25 poles male Sub-D connector	
		Pin number
White		1
Brown		2
Green		3
Yellow		4
Grey		5
Pink		6
Blue		7
Red		8
Black		9
Violet		10
Grey-Pink		11
Red-Blue		12
White-Green		13
Brown-Green		14
White-Yellow		15
Yellow-Brown		16
White-Grey		17
Grey-Brown		18
White-Pink		19
Pink-Brown		20
White-Blue		21
Brown-Blue		22
White-Red		23
Brown-Red		24
White-Black		25
Shield		Connected to Sub-D

Notes	
Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data	
Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	2 A

Connection data	
Cable type	LiYCY
Color code	per DIN VDE 47100
Connection 1	
Pluggable connector	D-subminiature male connector
Pole number 1	25
Connection type	System
Wire cross-section	0.25 mm²



Connection 2	
Connector	open-ended
Connection type	open-ended

Physical data	
Cable length	3 m

Material data	
Fire load	0 MJ
Weight	1.1 g

Environmental requirements	
Ambient temperature (operation)	-20 ... +50 °C

Commercial data		
PU (SPU)		1 pcs
Packaging type		Box
Country of origin		FR
GTIN		4050821835486
Customs tariff number		85444290900

Product Classification		
UNSPSC		26121604
ETIM 9.0		EC001855
ETIM 8.0		EC001855
ECCN		NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 706-100/525-300	