

GEN II TESLA MOBILE CONNECTOR ADAPTERS BY AC WORKS®



Tesla Gen I Mobile Connector

Tesla Gen II Mobile Connector



Charging Limits

Our G2 adapters have a built-in chip that auto sets the charging limit to 80% of the total amperage of your outlet. This helps to avoid tripping your breaker while charging your vehicle at the most efficient rate. There is also a built-in temperature monitor that detects faulty outlets, keeping you and your cord safe.


RATING	NEMA	SOURCE	HEAVY-DUTY CHARGING EXTENSION
15A 125V		HOUSEHOLD	HD515PR 12 AWG SD515PR 10 AWG SD515520 10 AWG

		RATING	NEMA	SOURCE	FLEXIBLE ADAPTER	15 FOOT ADAPTERS	HEAVY-DUTY CHARGING EXTENSION				
20A	250V			6-20P	AIR CONDITIONER		G2EV620PT-16A 16A Charging Limit		G2EV620-16A-15 16A Charging Limit		S620PR 12 AWG SD620PR 10 AWG
				L6-20P	INDUSTRIAL LOCKING		G2EVL620PT-16A 16A Charging Limit		G2EVL620-16A-15 16A Charging Limit		L620PR 12 AWG
	125/250V			L14-20P	4-PRONG LOCKING		G2EVL1420PT-16A 16A Charging Limit		G2EVL1420-16A-15 16A Charging Limit		L1420PR 12 AWG
				L15-20P	INDUSTRIAL LOCKING		G2EVL1520PT-16A 16A Charging Limit		G2EVL1520-16A-15 16A Charging Limit		L1520PR 12 AWG
	250V 3-PHASE			L21-20P	INDUSTRIAL LOCKING		G2EVL2120PT-16A 16A Charging Limit		G2EVL2120-16A-15 16A Charging Limit		L2120PR 12AWG
30A	125V			L5-30P	3-PRONG LOCKING		G2EVL530PT-24A 24A Charging Limit		G2EVL530-24A-15 24A Charging Limit		SDL530PR 8 AWG L530PR 10 AWG
				TT-30P	RV PARK		G2EVTT30-24A 24A Charging Limit		G2EVTT-24A-15 24A Charging Limit		TT30PR-RU 10 AWG TT30PR 10AWG

NEED HELP?

24/7 Customer Service (414) 434-2220
Text Questions to (414) 323-3240
Email: Info@ACConnectors.com
To Purchase: www.ACWORKS.com
Version 1, ©2024 Cordtec Power Corp.



30A	250V		6-30P	HVAC		G2EV630PT-24A 24A Charging Limit		G2EV630-24A-15 24A Charging Limit	N/A
			L6-30P	INDUSTRIAL LOCKING		G2EVL630PT-24A 24A Charging Limit	Coming Soon!	G2EVL630-24A-15 24A Charging Limit	L630PR 10 AWG
	125/250V		10-30P	3-PRONG OLD DRYER OUTLET		G2EV1030PT-24A 24A Charging Limit		G2EV1030-24A-15 24A Charging Limit	1030PR 10AWG
			14-30P	4-PRONG DRYER OUTLET		G2EV1430PT-24A 24A Charging Limit		G2EV1430-24A-15 24A Charging Limit	1430PR 10 AWG
			L14-30P	4-PRONG LOCKING		G2EVL1430PT-24A 24A Charging Limit		G2EVL1430-24A-15 24A Charging Limit	SDL1430PR 8AWG L1430PR 10 AWG
			L15-30P	INDUSTRIAL LOCKING		G2EVL1530PT-24A 24A Charging Limit	Coming Soon!	G2EVL1530-24A-15 24A Charging Limit	L1530PR 10 AWG
	250V		L21-30P	INDUSTRIAL LOCKING		G2EVL2130PT-24A 24A Charging Limit	Coming Soon!	G2EVL2130-24A-15 24A Charging Limit	L2130PR 10 AWG
	120/208V 3-PHASE								
50A	250V		6-50P	WELDER OUTLET		G2EV650PT-32A 32A Charging Limit		G2EV650-32A-15 32A Charging Limit	WD650PR 8 AWG
	125/250V		10-50P	OLD WELDER RANGE OUTLET		G2EV1050PT-32A 32A Charging Limit		G2EV1050-32A-15 32A Charging Limit	N/A
			14-50P	4-PRONG RANGE		G2EV1450PT-32A 32A Charging Limit		G2EV1450-32A-15 32A Charging Limit	1450PR 6 AWG
			SS2-50P	SHORE POWER		G2EVSS2PT-32A 32A Charging Limit	Coming Soon!	G2EVSS2-32A-15 32A Charging Limit	MSS2PR 6 AWG

Safety Switch
Convenience

With the AC WORKS® Safety Switch Y-Cable, conveniently swap between your dryer and EV charger, or other applications, using one switch.

EVY1030SW-036



(1) NEMA 10-30P to (2)
NEMA 10-30R 3-PRONG
DRYER

EVY1430SW-036



(1) NEMA 14-30P to (2)
NEMA 14-30P 4-PRONG
DRYER

NEED HELP?

24/7 Customer Service (414) 434-2220
Text Questions to (414) 323-3240
Email: Info@ACConnectors.com
To Purchase: www.ACWORKS.com
Version 1, ©2024 Cordtec Power Corp.

