TE Internal #: 2013499-1

B, Micro USB, 2.0, Receptacle, 5 Position, Top Mount, 1 Port, Right

Angle, Tape & Reel, Offset, Surface Mount, Cable-to-Board

View on TE.com >



Connectors > Audio & Video Connectors > USB Connectors











USB Type: **B**

USB Version: 2.0

Connector Profile: Micro

Connector & Housing Type: Receptacle

Contact Mating Area Plating Material Thickness

Number of Ports: 1

Features

Product Type Features

Integral Locking Latch	Without
USB Type	В
USB Version	2.0
Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Ports	1
Number of Positions	5
Body Features	
Shell Plating Finish	Bright
Shell Plating Material	Tin
Connector Profile	Micro
Contact Features	

.76 μm[30 μin]



Contact Mating Area Plating Material	Gold (Au)
Contact Current Rating (Max)	1.8 A
Termination Features	
Termination Post & Tail Length	.8 mm[.031 in]
Termination Method to PCB	Surface Mount
Mechanical Attachment	
Locking Feature	Without
PCB Mount Location	Top Mount
PCB Connector Seating	Offset
PCB Mount Retention Type	Straight Leg
Panel Mount Feature Type	Flange
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Thermoplastic
Housing Color	Black
Body Orientation	Right Angle
Centerline (Pitch)	.65 mm[.025 in]
Dimensions	
PCB Thickness (Recommended)	.8 – 1 mm[.031 – .039 in]
Usage Conditions	
Soldering Temperature (Max)	260 °C[500 °F]
Mating Cycles (Max)	10000
Operating Temperature Range	-30 - 85 °C[-22 - 185 °F]
Operation/Application	
Halogen Free	No
Assembly Process Feature	Without Pick and Place Cover
Circuit Application	Power & Signal
Industry Standards	
Moisture Sensitivity Level	1
Test Identification (TID)	61001336
UL Flammability Rating	UL 94V-0

Packaging Features



Packaging Quantity	1000
Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 245°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Customers Also Bought













TE Part #2434992-4 SOCKET E2 TFLM KIT WITH COVER







TE Part #2314177-1 HEAT SINK CLIP, QSFP28 1XN, LOWER PROF TE Part #2352533-1 HEAT SINK CLIP QSFP28/QSFP_DD

Documents

Product Drawings

MICRO USB, TYPE B

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2013499-1_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2013499-1_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2013499-1_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

5-1773464-3_Quick_Reference_Guide_Micro_USB_Connectors

English

Product Specifications

Product Specification

Japanese

Instruction Sheets

Instruction Sheet (non U.S.)

B, Micro USB, 2.0, Receptacle, 5 Position, Top Mount, 1 Port, Right Angle, Tape & Reel, Offset, Surface Mount, Cable-to-Board



Japanese