




Z-PACK | Z-PACK 2mm HM

TE Internal #: 5646574-1
Hard Metric Backplane PCB Mount Receptacle, ≤1 Gb/s, 25
Column, 5 Row, Mezzanine, 125 Position, 2 mm [.078 in] Centerline,
Right Angle, Z-PACK 2mm HM

[View on TE.com >](#)

Connectors > PCB Connectors > Backplane Connectors > Hard Metric Backplane Connectors >

HM Receptacle Connector: Traditional Backplane, Coplanar, 2mm



PCB Connector Type: **PCB Mount Receptacle**

Data Rate: **≤1 Gb/s**

Number of Columns: **25**

Number of Rows: **5**

Backplane Architecture: **Mezzanine**

[All HM Receptacle Connector: Traditional Backplane, Coplanar, 2mm \(48\)](#)

Features

Product Type Features

Connector & Contact Terminates To	Printed Circuit Board
Backplane Interface Type	2mm HM
Connector System	Board-to-Board
PCB Connector Type	PCB Mount Receptacle
Sealable	No

Configuration Features

Number of Signal Positions	110, 125
Number of Columns	25
Number of Rows	5
Backplane Architecture	Mezzanine
Number of Positions	125
PCB Mount Orientation	Right Angle



Signal Characteristics

Crosstalk Version	Standard
Data Rate	≤1 Gb/s

Body Features

Primary Product Color	Gray
-----------------------	------

Contact Features

Contact Underplating Material	Nickel
Contact Base Material	Phosphor Bronze
CompactPCI Designation	None
PCB Contact Termination Area Plating Material	Tin
Feedthrough Post Length	3.3 mm
Contact Type	Socket
Contact Mating Area Plating Material	Gold (Au), Gold Flash over Palladium Nickel
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
Contact Current Rating (Max)	1.5 A

Termination Features

Termination Method to PCB	Through Hole - Press-Fit
---------------------------	--------------------------

Mechanical Attachment

Connector Mounting Type	Board Mount
Mating Alignment Type	Polarizing Peg

Housing Features

Housing Material	Polyester GF
Centerline (Pitch)	2 mm[.078 in]

Dimensions

Backplane Module Length	49.88 mm
-------------------------	----------

Usage Conditions

Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
-----------------------------	----------------------------

Operation/Application

Shielded	No
Circuit Application	Power & Signal

Industry Standards

--	--



UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	11
Packaging Method	Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2170311-2 Z-PACK 2MM HM TYPE A/B 125P	TE Part # 2170336-1 Z-PACK 2MM HM TYPE A/B 169P	 TE Part # 5646731-1 Z-PACK 2MM HM TYPE A/B 125P	TE Part # 6645246-1 2MM H.M. TYPE A/B PIN ASSEMBLY
---	---	--	--



TE Part # 1645592-1
Z-PACK 2MM HM TYPE A/B 169P

TE Part # 2392859-1
Z-PACK A/B REC ASY 125P 2MMHM EON

Also in the Series | Z-PACK 2mm HM

Board-to-Board Headers & Receptacles(46)

Connector Contacts(1)

Connector Hardware(91)

Hard Metric Backplane Connectors (264)

Power Contacts(1)

Rectangular Power Connectors(46)

Customers Also Bought

TE Part #154763-E
SMCB 12 M AB VV 7-03 CL * 0007 137 E004

TE Part #154809-E
SMCB 80 F AB VV 7-13 CL * H007 137 E002

TE Part #CONREV SMA008
RP-SMA Jack 50 Ohm PCB Through Hole

TE Part #CONMMCX002-SMD-T
MMCX Jack 50 Ohm PCB Surface Mount

TE Part #CON SMB001-SMD-G
SMB Jack 50 Ohm PCB Surface Mount

TE Part #2-1393236-1
V23092-A1024-A201

TE Part #1571300-3
TACT,RTANG,SMT,SEALED,GUID PIN, T/R

TE Part #1-1658549-5
FPH-2022G=FLXPAC HDR P 20 ST LF



Documents

Product Drawings

Z-PACK A/B REC ASY 125P 2MMHM

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_5646574-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_5646574-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_5646574-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English