




Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Ground**

Modular Terminal Block Product Type: **Screw Clamp Terminal Block**

Primary Product Color: **Green & Yellow**

Product Spacing: **8 mm [.315 in]**

Number of Positions: **2**

Features

Product Type Features

Modular Terminal Block Product Type	Screw Clamp Terminal Block
-------------------------------------	----------------------------

Configuration Features

Number of Levels	1
Gauge Type	A5-B5
Number of Circuits	1
Block Function	Ground
Number of Positions	2

Electrical Characteristics

Impulse Withstanding Voltage Rating (IEC)	8000 V
Dielectric Withstanding Voltage (Max)	2000 V
Voltage Rating (CSA)	300 V
Short-Time Withstanding Current Rating @ 1s	1200 A

Body Features

Product Weight	28.4 g[1.118 oz]
Primary Product Color	Green & Yellow

Mechanical Attachment

DIN Rail Mounting Type	TH35-15, TH35-7.5
------------------------	-------------------



Connector Mounting Type

DIN Rail

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Depth	52 mm
Tool Size	3.5 mm[.138 in]
Wire Stripping Length	13 mm[.512 in]
Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp	20 – 12 AWG
Main Circuit Capacity - Twin Ferrule per Screw Clamp	20 – 12 AWG
Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp	20 – 12 AWG
Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	24 – 6 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp	.5 – 10 mm²
Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp	.5 – 6 mm²
Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp	24 – 6 AWG
Product Height	80.7 mm
Product Length	52 mm[2.04 in]
Product Spacing	8 mm[.315 in]

Usage Conditions

Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]

Industry Standards

IP Rating	IP20
UL Flammability Rating	UL 94V-0

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250)



Candidate List Declared Against: JUNE 2025 (250)
Does not contain REACH SVHC

Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1SNA206682R0300
AJS9-GR



TE Part # 1SNA116540R2500
PC8-4



TE Part # 1SNK900653R0000
SC-JB8-3



TE Part # 1SNA206765R0000
AJS9-WH



TE Part # 1SNA400724R0300
PC8-R4



TE Part # 1SNA163313R2400
PC8-10



TE Part # 1SNK900655R0000
SC-JB8-5



TE Part # 1SNK900654R0000
SC-JB8-4

1SNK508151R0000

Screw Clamp Terminal Block, Ground, Green & Yellow, 8 mm [.315 in] Spacing, 2 Position, DIN Rail, -55 – 110 °C [-67 – 230 °F], ENTRELEC SNK



TE Part # 1SNA173888R2000
BP8.A4

TE Part # 1SNK908905R0000
JB8-5-R1

TE Part # 1SNK900657R0000
SC-JB8-3-OR

TE Part # 1SNK900658R0000
SC-JB8-4-OR

TE Part # 1SNA400843R0000
PC8-R6

TE Part # 1SNA206720R1400
AJS9-RD

TE Part # 1SNA400842R0000
PC8-R5

TE Part # 1SNK900102R0000
BAZH1

TE Part # 1SNA400849R0000
PC8-R7

TE Part # 1SNA400711R0600
PC8-R1

TE Part # 1SNK169999R0000
MC812PA

TE Part # 1SNK160011R0000
MC812PA 1->10 (x10) Horizontal

Also in the Series | ENTRELEC SNK

Modular Terminal Blocks(319)

Terminal Block & Strip Conducting
Accessories(67)

Terminal Block & Strip Insulating
Accessories(31)


Customers Also Bought

TE Part #1SNK516010R0000
ZS35

TE Part #1SNA166646R0500
CPT-1

TE Part #1SNK908302R0000
JB8-2

TE Part #1SNK506012R0000
ZS6-4S



Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK508151R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK508151R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK508151R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ENTRELEC Terminal Block - Master Catalog

ENTRELEC Terminal Block - Master Catalog

English

ZS10-PE-R1

English

SNK SERIES TERMINAL BLOCKS

English

ENTRELEC Terminal Blocks Catalogue (RUS)