

#### STRATO-THERM

TE Internal #: 329651

Yellow, Butt Splice, 12 – 10 AWG, 3 – 6 mm<sup>2</sup> Wire, 5180 – 13100


CMA, Fully Insulated, Serrated, Copper, 19.43 mm [.765 in] Length,

STRATO-THERM

View on TE.com >



Terminals & Splices > Splices



Splice Type: Butt Splice

Wire Size: 3-6 mm<sup>2</sup>

Sealable: No

Splice Features: Serrated

## **Features**

## **Product Type Features**

Splice Type	Butt Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Insulation Support

## **Configuration Features**

Compatible With Wire & Cable Type	Discrete Wire
Body Features	
Insulation Material	Polytetrafluoroethylene (PTFE)
Ring Material	Aluminum

Insulation Type Post-Insulated

Splice Features Serrated

Primary Product Color Yellow

#### **Contact Features**

50 μin



Terminal Plating Material	Gold
Contact Base Material	Copper
Barrel Type	Closed
Dimensions	
Recovered Inside Diameter	3.28 mm[.129 in]
Outside Diameter	5.61 mm[.221 in]
Wire Size	5180 – 13100 CMA
Compatible Insulation Diameter Range	3.88 mm[.153 in]
Barrel Inside Diameter	5.94 mm[.234 in]
Product Length	19.43 mm[.765 in]
Usage Conditions	
Insulation Option	Fully Insulated
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	25
Packaging Method	Package

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



#### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



## Also in the Series | STRATO-THERM







# Customers Also Bought















TE Part #624385-000 B-023-02CS2684

TE Part #ZPF00000000003340 66241-10 A

TE Part #901562-000 B-013-12CS2689

TE Part #ZPF00000000003341 66241-12 A

### **Documents**

### **Product Drawings**

PO INS STRATO BUTT S 12-10

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_329651\_C.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_329651\_C.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_329651\_C.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_329651\_C1.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_329651\_C1.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_329651\_C1.2d\_dxf.zip

English

3D PDF

English

Yellow, Butt Splice, 12 – 10 AWG, 3 – 6 mm² Wire, 5180 – 13100 CMA, Fully Insulated, Serrated, Copper, 19.43 mm [.765 in] Length, STRATO-THERM



By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

**Application Specification** 

English