# 1-5645955-2 ACTIVE

TE Internal #: 1-5645955-2

4.67 mm [.184 in] Socket Length, 1.32 mm [.052 in] PCB Hole, Bullet

Nose, .081 – .326 mm<sup>2</sup> Wire, 28 – 22 AWG, Cable-to-Board, Pin

Sockets

View on TE.com >



Connectors > Socket Connectors > Pin Sockets > Miniature Spring Sockets: Bullet Nose, Beryllium Copper, 4A











Socket Length: 4.67 mm [.184 in]

PCB Hole Diameter: 1.32 mm [ .052 in ]

Socket Sleeve Style: Bullet Nose

Wire Size: **28 – 22 AWG** 

All Miniature Spring Sockets: Bullet Nose, Beryllium Copper, 4A (14)

### **Features**

## **Product Type Features**

Connector & Contact Terminates To	Printed Circuit Board
Socket Sleeve Style	Bullet Nose
Connector System	Cable-to-Board
Sealable	No

## **Configuration Features**

## **Body Features**

Sleeve Plating Material	Tin
Sleeve Material	Copper

### **Contact Features**

Contact Spring Plating Material	Gold
Contact Base Material	Beryllium Copper
Contact Mating Area Plating Material Thickness	30 μm[30 μin]
Contact Spring Plating Thickness	.762 μm[30 μin]



Contact Current Rating (Max)	4 A
Termination Features	
Termination Method to PCB	Through Hole - Press-Fit
Termination Method to Wire & Cable	Solder
Insertion Method	Hand/Semi-Automatic/Automatic
Dimensions	
PCB Thickness (Recommended)	.79 – 3.18 mm[.031 – .125 in]
Socket Length	4.67 mm[.184 in]
PCB Hole Diameter	1.32 mm[.052 in]
Wire Size	28 – 22 AWG
Mating Pin Diameter Range	.36 – .66 mm[.014 – .026 in]
Usage Conditions	
Operating Temperature Range	-65 – 125 °C[-85 – 257 °F]
Operation/Application	
Solder Process Feature	Anti-Flux
Circuit Application	Power & Signal
Packaging Features	
Packaging Method	Reel
Packaging Quantity	10000
Other	
Spring Material	Beryllium Copper

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.



#### Solder Process Capability

Pin-in-Paste capable to 260°C

#### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



## **Customers Also Bought**





















### **Documents**

## **Product Drawings**

SOCKET, MIN-SPR B-N SN-AU SER-2

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_1-5645955-2\_O.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-5645955-2\_O.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-5645955-2\_O.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## **Product Specifications**

**Product Specification** 

English