



NOTES:

- 1. MATERIAL: SELF-EXTINGUISHED PLASTIC UL 94V-0, ABS.
- 2. OPERATION TEMPERATURE: -10°C TO 60°C

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X = ±.2 [5.08] FRACTIONS $.XX = \pm .02 [.51]$ ± 1/32 .XXX = ±.005 [.13] ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0

300 [7620] < L = +5%L / -0 ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY



an INFINITe brand

859 E. Park Avenue, Libertyville, IL 60048 Phone: 1.800.505.1363 Website: www.navepoint.com E-mail: sales@navepoint.com

TRANSTECTOR, INC ALL RIGHTS RESERVED. SHEET SCALE N/A

REV

Α

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF

SIZE CAGE CODE DRAWN BY ITEM NO. Α 7UTA6 00406825 **WZHANG**