# 5-1534796-9 ACTIVE

#### AMP DUOPLUG

TE Internal #: 5-1534796-9

Wire-to-Board, 9 Position, 2.5 mm [.098 in] Centerline, Insulation

Displacement (IDC), 1 Row, Natural, PA 6 GF, Standard Edge

Connectors

View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > Standard Edge Connectors











Connector System: Wire-to-Board

Number of Positions: 9

Centerline (Pitch): 2.5 mm [ .098 in ]

Termination Method to Wire & Cable: Insulation Displacement (IDC)

Number of Rows: 1

#### **Features**

#### **Product Type Features**

Connector System	Wire-to-Board
Connector & Housing Type	Receptacle
Connector & Contact Terminates To	Printed Circuit Board

#### **Configuration Features**

Card Entry Style	Side
Compatible With Wire & Cable Type	Discrete Wire
Number of Positions	9
Number of Rows	1
Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Right Angle

#### **Electrical Characteristics**

Operating Voltage 50 VAC, 250 VAC	50 VAC, 250 VAC	Operating Voltage
-----------------------------------	-----------------	-------------------

#### **Body Features**

Primary Product Color Natural



contact Features	
Contact Retention Within Housing	With
Contact Mating Area Plating Material Thickness	3 – 6 µm
Contact Mating Area Plating Material	Tin (Sn)
Contact Base Material	Copper Tin
PCB Contact Termination Area Plating Material	Tin
Contact Type	Socket
Contact Current Rating (Max)	2 A
ermination Features	
Termination Method to Wire & Cable	Insulation Displacement (IDC)
Mechanical Attachment	
PCB Mount Retention	Without
Contact Retention Type Within Housing	Locking Lance
Mating Retention	Without
Mating Alignment Type	Keyed
Mating Alignment	With
PCB Mount Alignment	Without
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	2.5 mm[.098 in]
Housing Material	PA 6 GF
Dimensions	
Compatible Insulation Diameter Range	1.2 – 1.6 mm[.047 – .063 in]
PCB Thickness (Recommended)	1.5 mm[.059 in]
Connector Height	7.3 mm[.287 in]
Wire Size	24 – 22 AWG
Jsage Conditions	
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
Operation/Application	
Circuit Application	Signal
ndustry Standards	



UL Flammability Rating	UL 94V-2
Glow Wire Rating	GWEPT 750°C (Without Flame)
Packaging Features	
Packaging Quantity	1540
Packaging Method	Tray

#### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts







### Customers Also Bought
















#### **Documents**

#### **Product Drawings**

AMP DUOPLUG MK2 CONNECTOR 9P

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5-1534796-9\_D.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-1534796-9\_D.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-1534796-9\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Wire-to-Board, 9 Position, 2.5 mm [.098 in] Centerline, Insulation Displacement (IDC), 1 Row, Natural, PA 6 GF, Standard Edge Connectors



### Datasheets & Catalog Pages

RAST Connector System Catalog

English

**Product Specifications** 

**Application Specification** 

English

Agency Approvals

**VDE Certificate** 

English