

IHV

TE Internal #: 2071429-1

General Purpose Contactor, DC, 1 Form X SPST-NO-DM, 350 A Contact Rating, 12 VDC Coil Voltage, 4 W Coil Power, Panel Mount,

Hermetically Sealed, IHV

View on TE.com >



Relays & Contactors > Electromechanical Relays











Relay & Contactor Type: General Purpose Contactor

Contact Current Rating: 350 A

Contact Arrangement: 1 Form X SPST-NO-DM

Current Type: DC

Coil Voltage Rating: 12 VDC

Features

Product Type Features

Relay & Contactor Type	General Purpose Contactor
Configuration Features	
Auxiliary Switch Contact Arrangement	Without
Contact Arrangement	1 Form X SPST-NO-DM
Contact Number of Poles	3
Electrical Characteristics	
Contact Switching Voltage (Max)	1800 VDC
Contact Current Rating	350 A
Coil Voltage Rating	12 VDC
Coil Power Rating DC	4 W
Insulation Initial Dielectric Between Contacts & Coil	2200 Vrms
Body Features	

Hermetically Sealed

Enclosure Type



Contact Features

Contact Material	Copper
Termination Features	
Main Termination & Connection Type	M6 Female
Coil Termination & Connection Type	Quick Connect Terminals
Mechanical Attachment	
Torque (Main)	98 in-lbs
Product Mounting Feature Type	Mounting Plate, Screw
Product Mount Type	Panel Mount
Dimensions	
Product Width	55.5 mm[2.185 in]
Product Length	69.8 mm
Product Height	101.6 mm[4 in]
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Environmental Ambient Temperature (Max)	85 °C[185 °F]
Operation/Application	
Current Type	DC
Packaging Features	
Packaging Method	Box
Other	
Contact Current Class	>200 - ≤500 A
Coil Power Rating Class	>3 - ≤10 W
Height Class (Mechanical)	>70 mm[>2.756 in]
Length Class (Mechanical)	>45 - ≤70 mm[>1.772 - ≤2.756 in]
Width Class (Mechanical)	>33 mm[>1.299 in]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted



	Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | IHV



Customers Also Bought























Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2071429-1_A2.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2071429-1_A2.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2071429-1_A2.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

IHV350 SERIES CONTACTOR

English

Agency Approvals

IHV350AANFA

General Purpose Contactor, DC, 1 Form X SPST-NO-DM, 350 A Contact Rating, 12 VDC Coil Voltage, 4 W Coil Power, Panel Mount, Hermetically Sealed, IHV



UL

English

UL

English