# CONSMA006.031 × OBSOLETE

SMA

TE Internal #: L9000270-01

TE Internal Description: SMA Jack 50 Ohm .031 PCB Edge Mount

View on TE.com >



Connectors > RF Connectors > Coax Connectors



RF Interface: SMA

RF Connector Style: Jack

Impedance:  $50 \Omega$ 

RF Connector Coupling Mechanism: Threaded Operating Frequency Range: 0 – 12.4 GHz

## **Features**

## **Product Type Features**

Connector Product Type	Connector Assembly
RF Interface	SMA
RF Connector Style	Jack
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

## **Configuration Features**

PCB Mount Orientation	Edge
Number of Positions	1
Number of Coaxial Contacts	1

#### **Electrical Characteristics**

Impedance $50 \Omega$
-----------------------

## **Body Features**

Body Material	Brass
Body Material Finish	Plated
Body Plating Material	Nickel

#### **Contact Features**

RF Connector Center Contact Plating Material	Gold (Au)
RF Connector Center Contact Material	Brass



## **Termination Features**

Termination Method to Wire & Cable	Solder
Mechanical Attachment	
RF Connector Coupling Mechanism	Threaded
Connector Mounting Type	Board Mount
RF Contact Captivation Method	Mechanical
Detent	Without
Housing Features	
Body Orientation	Straight
Operation/Application	
Circuit Application	Signal
Operating Frequency Range	0 – 12.4 GHz
Packaging Features	
Packaging Quantity	100
Packaging Method	Bulk
Other	
Lockwasher Material	Brass
Dielectric Material	Polytetrafluoroethylene (PTFE)

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Yet Reviewed
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Not reviewed for China RoHS compliance
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

# Also in the Series | SMA



Battery Holders(1)



Connector Adapters & Connector Savers(8)



Connector Caps & Covers(3)



Connector Hardware(2)



Connector Strain Relief(1)



RF Cable Assemblies(119)



RF Terminators(1)

# Customers Also Bought























# **Documents**

Datasheets & Catalog Pages

SMA FEMALE EDGE MULTI-MOUNT FOR 0.031INCH THICK BOARD

English