AMP | BNC

TE Internal #: 331350

TE Internal Description: BNC PLUG, PTFE

Mil-Spec: [-] View on TE.com >



Connectors > RF Connectors > Coax Connectors



RF Interface: BNC

RF Connector Style: Plug

RF Connector Mated Outer Diameter (Approximate): 14.53 mm [.572 in]

Impedance: 50Ω

RF Connector Coupling Mechanism: Bayonet

Features

Product Type Features

Connector Seal & Plug Type	Interface Seal
RF Interface	BNC
RF Connector Style	Plug
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Configuration Features	

Number of Positions	1
Number of Coaxial Contacts	1

Electrical Characteristics

Impedance	50 Ω
·	

Body Features

Body Material	Brass
Body Material Finish	Plated
Body Plating Material	Silver

Contact Features

Crimp Type	Dual Crimp
RF Connector Center Contact Underplating Material	Copper
RF Connector Center Contact Plating Material	Gold (Au)



RF Connector Center Contact Material	Brass
Termination Features	
Termination Method to Wire & Cable	Crimn

Mechanical Attachment

RF Connector Coupling Mechanism	Bayonet
RF Contact Captivation Method	Mechanical

Housing Features

Body Orientation	Straight
200,90000000000000000000000000000000000	o e. a. g. re

Dimensions

RF Connector Mated Outer Diameter (Approximate)	14.53 mm[.572 in]	
Ri Connector Mated Outer Diameter (Approximate)	14.55 11111[.57 2 111]	

Usage Conditions

Insulation Option	Uninsulated	
Operation/Application		

Operation/Application

Operating Frequency Range	4 GHz
---------------------------	-------

Packaging Features

Packaging Method	Package	
------------------	---------	--

Other

Coupling Nut Base Material	Brass
Grade	Military
Dielectric Material	Polytetrafluoroethylene (PTFE)

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
(2 C) (2 S) P Ari	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Pb (3.7% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.



Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free


Solder Process Capability

Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Also in the Series | BNC







Customers Also Bought





















DIECAST STRAIN RELIEF KIT,SZ 2

TE Part #03561310-000 LVDT 250 MHR-3882 ASSEMBLY

Documents

CAD Files

Customer View Model

ENG_CVM_CVM_331350_BR.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_331350_BR.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_331350_BR.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Instruction Sheets

COAXICON 50-Ohm RF Series BNC Plug Connectors 225395-(), 225886-(), and 331350-()

English

Instruction Sheet (U.S.)

English