




APPROVED: \_\_\_\_\_  
DATE: \_\_\_\_\_ TITLE: \_\_\_\_\_

Rev	AWO #	Description	Date	Appr
-		RELEASED	4/1/05	
A		REVISED SHAPE	12/18/12	



SPECIFICATIONS:

Material:  
Insulator: PBT, glass reinforced, rated UL 94V-0  
Insulator color: Black  
Contacts: Phosphor Bronze  
Plating:  
G = Gold flash over Nickel underplate overall  
T = Tin over Copper underplate overall  
Electrical:  
Operating voltage: 250 VAC max  
Current rating: 1 Amp max  
Contact resistance: 20 mohms max  
Insulation resistance: 5,000 Mohms min  
Dielectric withstanding voltage: 1,000 VAC for 1 minute  
Temperature Rating:  
Operating temperature: -55°C to +105°C  
Environmental:  
Lead free, RoHS compliant



**ADAM TECH**

909 Rahway Avenue, Union, NJ 07083  
Phone: 908-687-5000 Fax: 908-687-5710

TITLE  
.079 [2.00] MINI SHUNT, OPEN TOP  
.138 [3.50] HEIGHT

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED							
INCHES				HOLES			
.X ± .10				ØX ± .10			
.XX ± .020				ØXXX ± .015			
.XXX ± .015				ØXXX ± .010			
APPROVALS				DATE			
DRAWN				SS			
				4/1/05			
CHECKED							
APPROVED							
SIZE		PART NO.		SCALE: NTS		SHEET 1 OF 1	
X		MS2B-X				REV. A	
REF:							