



STICKER
PIN.5 WHITE/BLUE
PIN.4 BLUE
PIN.1 WHITE/ORANGE
PIN.2 ORANGE
PIN.3 WHITE/GREEN
PIN.6 GREEN
PIN.7 WHITE/BROWN
PIN.8 BROWN

NOTES:

CAVITY CONFIRMS TO FCC RULES AND REGULATION PART 68, SUBPART F.

1. CONNECTOR MATERIALS:

- 1.1 HOUSING: ABS, WITH GLASS FIBER, UL94V-0, STANDARD COLOR-WHITE.
- 1.2 INSERT HOUSING: PBT, WITH GLASS FIBER, UL94V-0, STANDARD COLOR-BLACK.
- 1.3 IDC HOUSING: PC/ ABS, WITH GLASS FIBER, UL94V-0, STANDARD COLOR-WHITE.
- 1.4 IDC COVER: PBT, WITH GLASS FIBER, UL94V-0, STANDARD COLOR-BLACK.
- 1.5 REAR COVER: ABS, WITH GLASS FIBER, UL94V-0, STANDARD COLOR-WHITE.
- 1.6 TOP COVER: PBT, WITH GLASS FIBER, UL94V-0, STANDARD COLOR-WHITE.
- 1.7 CONTACTS : PHOSPHOR BRONZE.
- 1.8 IDC CONTACTS: PHOSPHOR BRONZE.
- 1.9 PCB: FR4, THICKNESS: 1.6mm.

2. FINISH:

- 2.1 CONTACT: 50μ" [1.27 μm] GOLD PLATED ON CONTACT AREA, GOLD FLASH ON SOLDER TAIL, 50μ" [1.27 μm] MIN. NICKEL UNDERPLATED OVERALL.
- 2.2 IDC CONTACTS: 150μ" [3.81 μm] TIN PLATED, 50μ" [1.27 μm] MIN. NICKEL UNDERPLATED OVERALL.



X:X	±0.30	APPD: Jessie	TELEWIRE TECHNOLOGY CO., LIMITED	
X:XX	±0.25	CHKD: Kevin		
X:XXX	±0.05	DR: Michael	KEYSTONE JACK	
ANGLES	±1°	UNIT: mm	PART NO. :	TWKS6-B02-9934C
	SCALE: 2/1	SHEET: 2/2	REV: A	DWG NO. : TWKS6-B02-9934C