SPLICE

TE Internal #: 63625-1


Pigtail Splice / Thru Splice, 13 – 8 AWG, 2.5 – 8.1 mm² Wire, 5000 – 16000 CMA, Uninsulated, Brass, 0 Serration, 6.78 mm [.267 in]


Length, SPLICE

View on TE.com >



Terminals & Splices > Splices











Splice Type: Pigtail Splice, Thru Splice

Wire Size: 5000 – 16000 CMA

Sealable: No

Features

Product Type Features

Splice Type	Pigtail Splice, Thru Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support
Configuration Features	
Number of Serrations	0
Compatible With Wire & Cable Type	Discrete Wire
Body Features	
Body Features Product Weight	.739 g[.026 oz]
	.739 g[.026 oz]
Product Weight	.739 g[.026 oz] Brass
Product Weight Contact Features	
Product Weight Contact Features Contact Base Material	Brass



Wire Size	5000 – 16000 CMA
Terminal Material Thickness	.64 mm[.025 in]
Product Length	6.78 mm[.267 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	

3500

Strip

Product Compliance

Packaging Quantity

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on



requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









Also in the Series | SPLICE



Crimp Wire Pins, Tabs & Ferrules(1)



Splices(63)

Customers Also Bought
























Documents

Product Drawings

SPLICE 5000-16000 .025 BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_63625-1_H_c-63625-1-h.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_63625-1_H_c-63625-1-h.3d_igs.zip

English

Customer View Model

ENG_CVM_63625-1_H_c-63625-1-h.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English