LGH

TE Internal #: 860267-1

6 Position Circular Power Connector, Lead Assembly, 27000 VDC, Wire-to-Wire, Wire & Cable, Plug, Pin, -55 – 125 °C [-67 – 257 °F],

Package

View on TE.com >



Connectors > Power Connectors > Circular Power > Circular Power Connectors



Connector Product Type: Lead Assembly

Operating Voltage: 27000 VDC

Connector System: Wire-to-Wire

Number of Positions: 6

Sealable: No

Features

Product Type Features

Froduct Type Features	
Connector Product Type	Lead Assembly
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Plug
Configuration Features	
Number of Positions	6
Electrical Characteristics	
Operating Voltage	27000 VDC
Body Features	
Positive Stop Ferrule	Without
Contact Features	
Contact Type	Pin
Mechanical Attachment	
Panel Mount Feature Type	Retaining Ring
Usage Conditions	
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]



Operation/Application

Shielded	No
Packaging Features	
Packaging Quantity	1
Packaging Method	Package

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Pb (3.7% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Customers Also Bought





TE Part #CAT-FSS0002 3/4BSP MALE X FEMALE WATER FLOW SWITCH



TE Part #62061-2 110 FASTON TAB BR




TE Part #62572-6 FF 110 REC 20-16AWG TPBR




TE Part #1-87215-2 06 MODII HDR DRST UNSHRD .100



TE Part #160668-2 110 FASTIN FASTON,REC.,20-16 AWG, PTBR



TE Part #1-640513-0 15P MR II CAP HSG V0



TE Part #643067-4 04P MTA156 CMOLDED COVER



TE Part #1052422-1 2052 0000 02,SMA FM JACK RECPT



TE Part #6-2176070-8 3521 6K2 1% 2W



TE Part #6-2176453-8 CPF 0201 28K7 0.1% 25ppm 1K RL

Documents

Product Drawings

LGH-6 PIN HV PLUG ASY

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_860267-1_R.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_860267-1_R.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_860267-1_R.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Instruction Sheets

6 Position Circular Power Connector, Lead Assembly, 27000 VDC, Wire-to-Wire, Wire & Cable, Plug, Pin, -55 – 125 °C [-67 – 257 °F], Package



Instruction Sheet (U.S.)

English