



Multiple Pressure Ranges Available

- Transmit Long Distances
- Easy 3-Step Setup Process

Sensocon's® LoRaWAN® Wireless Pressure Sensors provide accurate and reliable measurements suitable for a wide range of applications. They leverage the robust LoRaWAN protocol to transmit data efficiently over long distances, securely and dependably.




Gateway

Applications

- HVAC Systems
- Filter Monitoring
- · Fume Hoods
- · Clean Rooms
- · Isolation Rooms
 - **Biological Safety Cabinets**
 - Paint Booths
- · Dust Collectors

DIMENSIONS



MODEL NUMBERS

Wireless Sensors

Model Number WS-DP01	Type Differential	Pressure Range 0-0.5"wc	Max Pressure 1.0 PSI	Accuracy +/- 1% FS*
WS-DP02	Differential	0-1"wc	1.0 PSI	+/- 1% FS*
WS-DP03	Differential	0-2"wc	1.5 PSI	+/- 1% FS*
WS-DP04	Differential	0-5"wc	1.5 PSI	+/- 1% FS*
WS-DP06	Differential	0-8"wc	1.5 PSI	+/- 1% FS*
WS-DP10	Differential	0-20"wc	4.5 PSI	+/- 1% FS*
WS-DP15	Differential	0-1 PSI	12 PSI	+/- 1% FS*

Graphs

Also available in multi-variable e.g. pressure + humidity/temperature + voltage. See www.sensocon.com for more details.

SPECIFICATIONS

Battery Type: CR123A (x2) Frequency Bands: US915

Wireless Technology: LoRaWAN Class A Max Receive Sensitivity: -130dBm Wireless Range: Up to 10 miles* Minimum Interval: 10 minutes Battery Life: 2.5 to 5 years Antenna: External Antenna Wireless Security: AES-128

Operating Temperature: -4° to 149°F

(-20° to 65°C)

Enclosure Rating: IP 65

Weight: 90g


SENSOGRAF

EASY TO SET UP - EASY TO USE



- New sensor setup
- Trending / dashboards
- Data storage
- Set up notifications
- Sampling interval changes





Set up Sensors in Minutes: Designed for simplicity, ease of installation and trouble-free use.



Trend

Gain Insights: Use Sensograf™ to visualize data via customizable dashboards.



Alert

Know When Something Isn't Right: Easily set up text and/or email alerts to notify key personnel when predefined conditions are met.



Act

Information Where and How Needed: Customize reporting interval to balance power consumption and data frequency needs.

^{*} Higher accuracy availble upon request

^{*}Clear line-of-sight. Transmit distances will vary.