

# 3.3V / 5V 1:5 Differential ECL/PECL/HSTL Clock Driver MC100EP14

## Description

The MC100EP14 is a low skew 1-to-5 differential driver, designed with clock distribution in mind, accepting two clock sources into an input multiplexer. The ECL/PECL input signals can be either differential or single-ended (if the  $V_{BB}$  output is used). HSTL inputs can be used when the LVEP14 is operating under PECL conditions.

The EP14 specifically guarantees low output-to-output skew. Optimal design, layout, and processing minimize skew within a device and from device to device.


To ensure that the tight skew specification is realized, both sides of any differential output need to be terminated even if only one output is being used. If an output pair is unused, both outputs may be left open (unterminated) without affecting skew.

The common enable ( $\overline{EN}$ ) is synchronous, outputs are enabled/disabled in the LOW state. This avoids a runt clock pulse when the device is enabled/disabled as can happen with an asynchronous control. The internal flip flop is clocked on the falling edge of the input clock, therefore all associated specification limits are referenced to the negative edge of the clock input.

The  $V_{BB}$  pin, an internally generated voltage supply, is available to this device only. For single-ended input conditions, the unused differential input is connected to  $V_{BB}$  as a switching reference voltage.  $V_{BB}$  may also rebias AC coupled inputs. When used, decouple  $V_{BB}$  and  $V_{CC}$  via a 0.01  $\mu$ F capacitor and limit current sourcing or sinking to 0.5 mA. When not used,  $V_{BB}$  should be left open.


## Features

- 400 ps Typical Propagation Delay
- 100 ps Device-to-Device Skew
- 25 ps Within Device Skew
- Maximum Frequency > 2 GHz Typical
- The 100 Series Contains Temperature Compensation
- PECL and HSTL Mode:  
 $V_{CC} = 3.0$  V to 5.5 V with  $V_{EE} = 0$  V
- NECL Mode:  
 $V_{CC} = 0$  V with  $V_{EE} = -3.0$  V to  $-5.5$  V
- Open Input Default State
- These are Pb-Free Devices



TSSOP-20  
DT SUFFIX  
CASE 948E

## MARKING DIAGRAM\*




(Note: Microdot may be in either location)

\*For additional marking information, refer to Application Note [AND8002/D](#).

## ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

# MC100EP14



**WARNING:** All  $V_{CC}$  and  $V_{EE}$  pins must be externally connected to Power Supply to guarantee proper operation.

**Figure 1. TSSOP-20 (Top View) and Logic Diagram**

**Table 1. PIN DESCRIPTION**

| Pin                           | Function                           |
|-------------------------------|------------------------------------|
| CLK0*, $\overline{CLK0}^{**}$ | ECL/PECL/HSTL CLK Input            |
| CLK1*, $\overline{CLK1}^{**}$ | ECL/PECL/HSTL CLK Input            |
| Q0:4, $\overline{Q0:4}$       | ECL/PECL Outputs                   |
| CLK_SEL*                      | ECL/PECL Active Clock Select Input |
| $\overline{EN}^*$             | ECL Sync Enable                    |
| $V_{BB}$                      | Reference Voltage Output           |
| $V_{CC}$                      | Positive Supply                    |
| $V_{EE}$                      | Negative Supply                    |

\* Pins will default low when left open.

\*\* Pins will default to  $V_{CC}/2$  when left open.

**Table 2. FUNCTION TABLE**

| CLK0 | CLK1 | CLK_SEL | $\overline{EN}$ | Q  |
|------|------|---------|-----------------|----|
| L    | X    | L       | L               | L  |
| H    | X    | L       | L               | H  |
| X    | L    | H       | L               | L  |
| X    | H    | H       | L               | H  |
| X    | X    | X       | H               | L* |

\* On next negative transition of CLK0 or CLK1

# MC100EP14

**Table 3. ATTRIBUTES**

| Characteristics                                               | Value                                                     |                             |
|---------------------------------------------------------------|-----------------------------------------------------------|-----------------------------|
| Internal Input Pulldown Resistor                              | 75 kΩ                                                     |                             |
| Internal Input Pullup Resistor                                | 37.5 kΩ                                                   |                             |
| ESD Protection                                                | Human Body Model<br>Machine Model<br>Charged Device Model | > 4 kV<br>> 200 V<br>> 2 kV |
| Moisture Sensitivity, Indefinite Time Out of Drypack (Note 1) | Pb Pkg                                                    | Pb-Free Pkg                 |
| TSSOP-8                                                       | Level 1                                                   | Level 1                     |
| Flammability Rating                                           | Oxygen Index: 28 to 34                                    | UL 94 V-0 @ 0.125 in        |
| Transistor Count                                              | 357 Devices                                               |                             |
| Meets or exceeds JEDEC Spec EIA/JESD78 IC Latchup Test        |                                                           |                             |

1. For additional information, see Application Note [AND8003/D](#).

**Table 4. MAXIMUM RATINGS**

| Symbol           | Parameter                                          | Condition 1                                    | Condition 2                                                          | Rating      | Unit         |
|------------------|----------------------------------------------------|------------------------------------------------|----------------------------------------------------------------------|-------------|--------------|
| V <sub>CC</sub>  | PECL Mode Power Supply                             | V <sub>EE</sub> = 0 V                          |                                                                      | 6           | V            |
| V <sub>EE</sub>  | NECL Mode Power Supply                             | V <sub>CC</sub> = 0 V                          |                                                                      | -6          | V            |
| V <sub>I</sub>   | PECL Mode Input Voltage<br>NECL Mode Input Voltage | V <sub>EE</sub> = 0 V<br>V <sub>CC</sub> = 0 V | V <sub>I</sub> ≤ V <sub>CC</sub><br>V <sub>I</sub> ≥ V <sub>EE</sub> | 6<br>-6     | V<br>V       |
| I <sub>out</sub> | Output Current                                     | Continuous<br>Surge                            |                                                                      | 50<br>100   | mA<br>mA     |
| I <sub>BB</sub>  | V <sub>BB</sub> Sink/Source                        |                                                |                                                                      | ± 0.5       | mA           |
| T <sub>A</sub>   | Operating Temperature Range                        |                                                |                                                                      | -40 to +85  | °C           |
| T <sub>stg</sub> | Storage Temperature Range                          |                                                |                                                                      | -65 to +150 | °C           |
| θ <sub>JA</sub>  | Thermal Resistance (Junction-to-Ambient)           | 0 lfpm<br>500 lfpm                             | TSSOP-20<br>TSSOP-20                                                 | 140<br>100  | °C/W<br>°C/W |
| θ <sub>JC</sub>  | Thermal Resistance (Junction-to-Case)              | Standard Board                                 | TSSOP-20                                                             | 23 to 41    | °C/W         |
| T <sub>sol</sub> | Wave Solder                                        | <2 to 3 sec @ 248 °C                           |                                                                      | 265         | °C           |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

# MC100EP14

**Table 5. 100EP DC CHARACTERISTICS, PECL**  $V_{CC} = 3.3\text{ V}$ ,  $V_{EE} = 0\text{ V}$  (Note 2)

| Symbol      | Characteristic                                                             | -40°C                                     |      |      | 25°C        |      |      | 85°C        |      |      | Unit |
|-------------|----------------------------------------------------------------------------|-------------------------------------------|------|------|-------------|------|------|-------------|------|------|------|
|             |                                                                            | Min                                       | Typ  | Max  | Min         | Typ  | Max  | Min         | Typ  | Max  |      |
| $I_{EE}$    | Power Supply Current                                                       | 45                                        | 55   | 65   | 48          | 58   | 68   | 52          | 62   | 72   | mA   |
| $V_{OH}$    | Output HIGH Voltage (Note 3)                                               | 2155                                      | 2280 | 2405 | 2155        | 2280 | 2405 | 2155        | 2280 | 2405 | mV   |
| $V_{OL}$    | Output LOW Voltage (Note 3)                                                | 1305                                      | 1480 | 1605 | 1305        | 1480 | 1605 | 1305        | 1480 | 1605 | mV   |
| $V_{IH}$    | Input HIGH Voltage (Single-Ended)                                          | 2075                                      |      | 2420 | 2075        |      | 2420 | 2075        |      | 2420 | mV   |
| $V_{IL}$    | Input LOW Voltage (Single-Ended)                                           | 1305                                      |      | 1675 | 1305        |      | 1675 | 1305        |      | 1675 | mV   |
| $V_{BB}$    | Output Voltage Reference                                                   | 1775                                      | 1875 | 1975 | 1775        | 1875 | 1975 | 1775        | 1875 | 1975 | mV   |
| $V_{IHCMR}$ | Input HIGH Voltage Common Mode Range (Differential Configuration) (Note 4) | 1.2                                       |      | 3.3  | 1.2         |      | 3.3  | 1.2         |      | 3.3  | V    |
| $I_{IH}$    | Input HIGH Current                                                         |                                           |      | 150  |             |      | 150  |             |      | 150  | μA   |
| $I_{IL}$    | Input LOW Current                                                          | $\overline{D}$ 0.5<br>$\overline{D}$ -150 |      |      | 0.5<br>-150 |      |      | 0.5<br>-150 |      |      | μA   |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

2. Input and output parameters vary 1:1 with  $V_{CC}$ .  $V_{EE}$  can vary +0.3 V to -2.2 V.

3. All loading with 50 Ω to  $V_{CC} - 2.0\text{ V}$ .

4.  $V_{IHCMR}$  min varies 1:1 with  $V_{EE}$ ,  $V_{IHCMR}$  max varies 1:1 with  $V_{CC}$ . The  $V_{IHCMR}$  range is referenced to the most positive side of the differential input signal.

**Table 6. 100EP DC CHARACTERISTICS, PECL**  $V_{CC} = 5.0\text{ V}$ ,  $V_{EE} = 0\text{ V}$  (Note 5)

| Symbol      | Characteristic                                                             | -40°C                                     |      |      | 25°C        |      |      | 85°C        |      |      | Unit |
|-------------|----------------------------------------------------------------------------|-------------------------------------------|------|------|-------------|------|------|-------------|------|------|------|
|             |                                                                            | Min                                       | Typ  | Max  | Min         | Typ  | Max  | Min         | Typ  | Max  |      |
| $I_{EE}$    | Power Supply Current                                                       | 45                                        | 55   | 65   | 48          | 58   | 68   | 52          | 62   | 72   | mA   |
| $V_{OH}$    | Output HIGH Voltage (Note 6)                                               | 3855                                      | 3980 | 4105 | 3855        | 3980 | 4105 | 3855        | 3980 | 4105 | mV   |
| $V_{OL}$    | Output LOW Voltage (Note 6)                                                | 3005                                      | 3180 | 3305 | 3005        | 3180 | 3305 | 3005        | 3180 | 3305 | mV   |
| $V_{IH}$    | Input HIGH Voltage (Single-Ended)                                          | 3775                                      |      | 4120 | 3775        |      | 4120 | 3775        |      | 4120 | mV   |
| $V_{IL}$    | Input LOW Voltage (Single-Ended)                                           | 3005                                      |      | 3375 | 3005        |      | 3375 | 3005        |      | 3375 | mV   |
| $V_{BB}$    | Output Voltage Reference                                                   | 3475                                      | 3575 | 3675 | 3475        | 3575 | 3675 | 3475        | 3575 | 3675 | mV   |
| $V_{IHCMR}$ | Input HIGH Voltage Common Mode Range (Differential Configuration) (Note 7) | 1.2                                       |      | 5.0  | 1.2         |      | 5.0  | 1.2         |      | 5.0  | V    |
| $I_{IH}$    | Input HIGH Current                                                         |                                           |      | 150  |             |      | 150  |             |      | 150  | μA   |
| $I_{IL}$    | Input LOW Current                                                          | $\overline{D}$ 0.5<br>$\overline{D}$ -150 |      |      | 0.5<br>-150 |      |      | 0.5<br>-150 |      |      | μA   |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

5. Input and output parameters vary 1:1 with  $V_{CC}$ .  $V_{EE}$  can vary +2.0 V to -0.5 V.

6. All loading with 50 Ω to  $V_{CC} - 2.0\text{ V}$ .

7.  $V_{IHCMR}$  min varies 1:1 with  $V_{EE}$ ,  $V_{IHCMR}$  max varies 1:1 with  $V_{CC}$ . The  $V_{IHCMR}$  range is referenced to the most positive side of the differential input signal.

# MC100EP14

**Table 7. 100EP DC CHARACTERISTICS, NECL**  $V_{CC} = 0\text{ V}$ ;  $V_{EE} = -5.5\text{ V}$  to  $-3.0\text{ V}$  (Note 8)

| Symbol      | Characteristic                                                              | -40°C        |       |       | 25°C         |       |       | 85°C         |       |       | Unit          |
|-------------|-----------------------------------------------------------------------------|--------------|-------|-------|--------------|-------|-------|--------------|-------|-------|---------------|
|             |                                                                             | Min          | Typ   | Max   | Min          | Typ   | Max   | Min          | Typ   | Max   |               |
| $I_{EE}$    | Power Supply Current                                                        | 45           | 55    | 65    | 48           | 58    | 68    | 52           | 62    | 72    | mA            |
| $V_{OH}$    | Output HIGH Voltage (Note 9)                                                | -1145        | -1020 | -895  | -1145        | -1020 | -895  | -1145        | -1020 | -895  | mV            |
| $V_{OL}$    | Output LOW Voltage (Note 9)                                                 | -1995        | -1820 | -1695 | -1995        | -1820 | -1695 | -1995        | -1820 | -1695 | mV            |
| $V_{IH}$    | Input HIGH Voltage (Single-Ended)                                           | -1225        |       | -880  | -1225        |       | -880  | -1225        |       | -880  | mV            |
| $V_{IL}$    | Input LOW Voltage (Single-Ended)                                            | -1995        |       | -1625 | -1995        |       | -1625 | -1995        |       | -1625 | mV            |
| $V_{BB}$    | Output Reference Voltage                                                    | -1525        | -1425 | -1325 | -1525        | -1425 | -1325 | -1525        | -1425 | -1325 | mV            |
| $V_{IHCMR}$ | Input HIGH Voltage Common Mode Range (Differential Configuration) (Note 10) | $V_{EE}+1.2$ |       | 0.0   | $V_{EE}+1.2$ |       | 0.0   | $V_{EE}+1.2$ |       | 0.0   | V             |
| $I_{IH}$    | Input HIGH Current                                                          |              |       | 150   |              |       | 150   |              |       | 150   | $\mu\text{A}$ |
| $I_{IL}$    | Input LOW Current CLK<br>CLK                                                | 0.5<br>-150  |       |       | 0.5<br>-150  |       |       | 0.5<br>-150  |       |       | $\mu\text{A}$ |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

8. Input and output parameters vary 1:1 with  $V_{CC}$ .

9. All loading with  $50\ \Omega$  to  $V_{CC} - 2.0\text{ V}$ .

10.  $V_{IHCMR}$  min varies 1:1 with  $V_{EE}$ ,  $V_{IHCMR}$  max varies 1:1 with  $V_{CC}$ . The  $V_{IHCMR}$  range is referenced to the most positive side of the differential input signal.

**Table 8. AC CHARACTERISTICS**  $V_{CC} = 0\text{ V}$ ;  $V_{EE} = -3.0\text{ V}$  to  $-5.5\text{ V}$  or  $V_{CC} = 3.0\text{ V}$  to  $5.5\text{ V}$ ;  $V_{EE} = 0\text{ V}$  (Note 11)

| Symbol                 | Characteristic                                                               | -40°C      |           |           | 25°C       |           |           | 85°C       |           |           | Unit |
|------------------------|------------------------------------------------------------------------------|------------|-----------|-----------|------------|-----------|-----------|------------|-----------|-----------|------|
|                        |                                                                              | Min        | Typ       | Max       | Min        | Typ       | Max       | Min        | Typ       | Max       |      |
| $V_{OPP}$              | Output Voltage Amplitude @ 2 GHz (Figure 2)                                  | 440        | 540       |           | 420        | 520       |           | 380        | 480       |           | GHz  |
| $t_{PLH}$<br>$t_{PHL}$ | Propagation Delay to Output Differential                                     | 275        | 330       | 400       | 275        | 375       | 450       | 280        | 380       | 480       | ps   |
| $t_{skew}$             | Within-Device Skew<br>Device-to-Device Skew (Note 12)                        |            | 25<br>100 | 35<br>125 |            | 30<br>150 | 45<br>175 |            | 40<br>175 | 50<br>200 | ps   |
| $t_s$<br>$t_h$         | Setup Time to CLK $\overline{EN}$ to CLK<br>Hold Time $\overline{EN}$ to CLK | 100<br>200 | 50<br>140 |           | 100<br>200 | 50<br>140 |           | 100<br>200 | 50<br>140 |           | ps   |
| $t_{JITTER}$           | Cycle-to-Cycle Jitter (Figure 2)                                             |            | 0.2       | < 1       |            | 0.2       | < 1       |            | 0.2       | < 1       | ps   |
| $V_{PP}$               | Minimum Input Swing                                                          | 150        | 800       | 1200      | 150        | 800       | 1200      | 150        | 800       | 1200      | mV   |
| $t_r/t_f$              | Output Rise/Fall Time (20%–80%)                                              | 105        | 155       | 205       | 145        | 200       | 270       | 150        | 225       | 300       | ps   |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

11. Measured using a 750 mV source, 50% duty cycle clock source. All loading with  $50\ \Omega$  to  $V_{CC} - 2.0\text{ V}$ .

12. Skew is measured between outputs under identical transitions.

## MC100EP14




Figure 2.  $F_{max}/Jitter$




Figure 3. Typical Termination for Output Driver and Device Evaluation  
(See Application Note AND8020/D – Termination of ECL Logic Devices.)

### ORDERING INFORMATION

| Device         | Package               | Shipping <sup>†</sup> |
|----------------|-----------------------|-----------------------|
| MC100EP14DTG   | TSSOP-20<br>(Pb-Free) | 75 Units / Rail       |
| MC100EP14DTR2G | TSSOP-20<br>(Pb-Free) | 2500 / Tape & Rail    |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, [BRD8011/D](#)

## MC100EP14

### Resource Reference of Application Notes

- AN1405/D** – ECL Clock Distribution Techniques
- AN1406/D** – Designing with PECL (ECL at +5.0 V)
- AN1503/D** – ECLinPS™ I/O SPICE Modeling Kit
- AN1504/D** – Metastability and the ECLinPS Family
- AN1568/D** – Interfacing Between LVDS and ECL
- AN1672/D** – The ECL Translator Guide
- AND8001/D** – Odd Number Counters Design
- AND8002/D** – Marking and Date Codes
- AND8020/D** – Termination of ECL Logic Devices
- AND8066/D** – Interfacing with ECLinPS
- AND8090/D** – AC Characteristics of ECL Devices

ECLinPS is a trademark of Semiconductor Components Industries, LLC dba “**onsemi**” or its affiliates and/or subsidiaries in the United States and/or other countries.


## MC100EP14

### REVISION HISTORY


| Revision | Description of Changes                           | Date     |
|----------|--------------------------------------------------|----------|
| 8        | Rebranded the Data Sheet to <b>onsemi</b> format | 7/9/2025 |

This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.





**TSSOP-20 WB**  
**CASE 948E**  
**ISSUE D**

DATE 17 FEB 2016



**NOTES:**

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 6.40        | 6.60 | 0.252     | 0.260 |
| B   | 4.30        | 4.50 | 0.169     | 0.177 |
| C   | ---         | 1.20 | ---       | 0.047 |
| D   | 0.05        | 0.15 | 0.002     | 0.006 |
| F   | 0.50        | 0.75 | 0.020     | 0.030 |
| G   | 0.65 BSC    |      | 0.026 BSC |       |
| H   | 0.27        | 0.37 | 0.011     | 0.015 |
| J   | 0.09        | 0.20 | 0.004     | 0.008 |
| J1  | 0.09        | 0.16 | 0.004     | 0.006 |
| K   | 0.19        | 0.30 | 0.007     | 0.012 |
| K1  | 0.19        | 0.25 | 0.007     | 0.010 |
| L   | 6.40 BSC    |      | 0.252 BSC |       |
| M   | 0°          | 8°   | 0°        | 8°    |

**RECOMMENDED  
SOLDERING FOOTPRINT\***


\*For additional information on our Pb-Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

**GENERIC  
MARKING DIAGRAM\***


A = Assembly Location  
L = Wafer Lot  
Y = Year  
W = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

|                         |                    |                                                                                                                                                                                     |
|-------------------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98ASH70169A</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>TSSOP-20 WB</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                                  |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)