











Similar to illustration



Similar to illustration

Color coding acc. to DIN VDE 47100		10 poles flat connector
		Pin number
White		1
Brown		2
Green		3
Yellow		4
Grey		5
Pink		6
Blue		7
Red		8
Black		9
Violet		10

Notes	
Note	When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.

Electrical data	
Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	1 A

Compatibility	
Omron	
Omron CJ1W	CJ1W-ID201 CJ1W-OD204



Connection data			
Cable type	LiYY	Connection 1	
Color code	per DIN VDE 47100	Pluggable connector	Pluggable connector per DIN 41651; female connector
		Pole number 1	10
		Connection type	System
		Wire cross-section	0.14 mm ²
Connection 2			
Connector	open-ended		
Connection type	open-ended		
Physical data			
Cable length	3 m		
Material data			
Fire load	0 MJ		
Weight	1.1 g		
Environmental requirements			
Ambient temperature (operation)	-20 ... +50 °C		
Commercial data			
PU (SPU)	1 pcs		
Packaging type	Box		
Country of origin	FR		
GTIN	4050821835219		
Customs tariff number	85444290900		
Product Classification			
UNSPSC	26121629		
ETIM 9.0	EC000237		
ETIM 8.0	EC000237		
ECCN	NO US CLASSIFICATION		
Environmental Product Compliance			
RoHS Compliance Status	Compliant, No Exemption		



Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 706-100/310-300	