2-1904058-5 ACTIVE

AMP+ | Mini K HV Precharge Relay

TE Internal #: 2-1904058-5

High Voltage Relay, DC, Monostable, 1 Form X SPST-NO-DM, 20 A Contact Rating, 12 VDC Coil Voltage, 400 VDC Contact Voltage,

Mini K HV Precharge Relay

View on TE.com >



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: High Voltage Relay

Coil Magnetic System: Monostable

Contact Arrangement: 1 Form X SPST-NO-DM

Current Type: DC

Contact Current Rating: 20 A

Features

Product Type Features

Contact Current Rating

Coil Voltage Rating

Relay & Contactor Type	High Voltage Relay
Configuration Features	
Coil Special Features	Without Resistor in Parallel
Contact Arrangement	1 Form X SPST-NO-DM
Electrical Characteristics	
Contact Limiting Making Current	20 A
Contact Limiting Breaking Current	20 A
Insulation Initial Dielectric Between Open Contacts	2000 Vrms

20 A

12 VDC

Contact Switching Voltage (Max)	450 VDC
Contact Voltage Rating	400 VDC

Coil Resistance	50 Ω
Coil Power Rating DC	2.9 W

Insulation Initial Dielectric Between Contacts & Coil 2000 Vrms

Body Features

Product Weight	17 g[.6 oz]
Enclosure Type	Flux Resistant Automatic Solder Capable &



$\backslash \backslash$	/as	ha	h	le
V 1	u	110	\sim	

Contact Features

Contact Material	Silver Alloy	

Termination Features

Main Termination & Connection Type	Solder Pins
Coil Termination & Connection Type	Solder Pins

Mechanical Attachment

Product Mount Type	Board Mount
--------------------	-------------

Dimensions

Product Width	20.7 mm[.815 in]
Product Length	25.55 mm[1.006 in]
Product Height	19.3 mm[.76 in]

Usage Conditions

Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Environmental Category of Protection	RTIII
Environmental Ambient Temperature (Max)	85 °C[185 °F]

Operation/Application

Solder Process	Wave Solder Capable
Coil Magnetic System	Monostable
Current Type	DC

Other

Coil Power Rating Class	>1.5 - ≤3 W
Contact Current Class	>16 - ≤25 A
Height Class (Mechanical)	>16 - ≤22 mm[>.63 - ≤.866 in]
Length Class (Mechanical)	>22 - ≤33 mm[>.866 - ≤1.299 in]
Width Class (Mechanical)	>16 - ≤22 mm[>.63 - ≤.866 in]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted



	Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Mini K HV Precharge Relay








Customers Also Bought






TE Part #175785-1 070 MLC CAP H ASSY DBL 20P NT.



TE Part #1-179277-5 DYNAMIC 3200 HDR ASSY 4P H



TE Part #321827 TERMINAL, SOLIS R 14-12 8



TE Part #735427-2 110 FASTON TAB TPBR



TE Part #776262-5 14POS,PIN DIA 1.3,HDR ASSY, 180DEG,COD 5



MOD2 STIFT M A-PIN



TE Part #2-1625971-0 HSA25 1R2 5%



TE Part #1802824-4 8POS,TAB0.63X0.63,HDR ASSY, 90DEG,COD 1



TE Part #1802824-6 8POS,TAB0.63X0.63,HDR ASSY, 90DEG,COD 3



TE Part #2208165-1 20POS, NANO MQS, HEADER ASSY, CODA

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1904058-5_A_c-2-1904058-5-a.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1904058-5_A_c-2-1904058-5-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1904058-5_A_c-2-1904058-5-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

Automotive Relay Application Notes

English

High Voltage Relays & Contactors, High Voltage Relay, Mini K HV Precharge Relay

English

High Voltage Relay, DC, Monostable, 1 Form X SPST-NO-DM, 20 A Contact Rating, 12 VDC Coil Voltage, 400 VDC Contact Voltage, Mini K HV Precharge Relay



Product Specifications

Definitions General Purpose Relays

English