# 1SNK805744R0000 V ACTIVE



## ENTRELEC | ENTRELEC SNK

TE Internal #: 1SNK805744R0000

Female Plug Terminal Block, Feed-Through, Blue, 5.2 mm [.204 in]


Spacing, 1 Position, Push-in, Signal, Cable Mount (Free-Hanging),

ENTRELEC SNK

View on TE.com >



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks











Block Function: Feed-Through

Modular Terminal Block Product Type: Female Plug Terminal Block

Primary Product Color: Blue

Product Spacing: 5.2 mm [.204 in]

Number of Positions: 1

## **Features**

## **Product Type Features**

Modular Terminal Block Product Type	Female Plug Terminal Block
Configuration Features	
Number of Levels	1
Gauge Type	A2 / 2.3 mm Dia.
Number of Poles	1
Number of Circuits	1
Block Function	Feed-Through
Number of Positions	1
Electrical Characteristics	
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	600 V
Impulse Withstanding Voltage Rating (IEC)	8000 V
Current Rating (IEC)	24 A
Current Rating (UL)	20 A
Current Rating (CSA)	20 A



Dielectric Withstanding Voltage (Max)	2200 V
Voltage Rating (IEC)	800 V
Voltage Rating (CSA)	600 V
Short-Time Withstanding Current Rating @ 1s	300 A
Operating Voltage	800 VAC
Body Features	
Product Weight	4.08 g[.143 oz]
Primary Product Color	Blue
Termination Features	
Termination Method to Wire & Cable	Push-in
Mechanical Attachment	
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	Polyamide 6.6
Dimensions	
Product Depth	42.9 mm[1.67 in]
Tool Size	3.5 mm[.138 in]
Wire Stripping Length	11 mm[.433 in]
Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp	26 – 12 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Spring Clamp	26 – 14 AWG
Main Circuit Capacity - 1 Insulated Ferrule per Spring Clamp	26 – 14 AWG
Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp	.22 – 2.5 mm²
Product Width	5.2 mm[.204 in]
Product Length	42.9 mm[1.67 in]
Product Height	23.8 mm[.91 in]
Product Spacing	5.2 mm[.204 in]
Wire Size	12 AWG
Usage Conditions	
Installation Temperature Range	-5 - 40 °C[23 - 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]
Operation/Application	



Circuit Application	Signal
Industry Standards	
IP Rating	IP20
UL Flammability Rating	UL 94V-0

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





TE Part # 1SNK900637R0000 VR-ZD









TE Part # 1SNK805025R0000 ZDK2.5-11-BL































Also in the Series | ENTRELEC SNK






Modular Terminal Blocks(319)



Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(31)

# Customers Also Bought






















## **Documents**

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1SNK805744R0000\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1SNK805744R0000\_A.3d\_igs.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_1SNK805744R0000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

**ENTRELEC Terminal Block - Master Catalog** 

**ENTRELEC Terminal Block - Master Catalog** 

English

**SNK SERIES TERMINAL BLOCKS** 

English

**Essential Entrelec Terminal Blocks** 

French

**Essential Entrelec Terminal Blocks** 

English

**Essential Entrelec Terminal Blocks** 

Japanese

## **Agency Approvals**

Bureau Veritas Marine and Offshore Certificate

English