



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Receptacle**

Connector System: **Board-to-Board**

Number of Positions: **10**

Number of Rows: **2**

Centerline (Pitch): **1.27 mm [.05 in]**

Features

Product Type Features

PCB Connector Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Number of Positions	10
Number of Rows	2
PCB Mount Orientation	Vertical
Board-to-Board Configuration	Orthogonal, Parallel

Electrical Characteristics

Operating Voltage	30 VAC
Insulation Resistance	5000 MΩ

Body Features



Primary Product Color	Black
-----------------------	-------

Contact Features

Mating Square Post Dimension	.38 mm[.015 in]
PCB Contact Termination Area Plating Material Thickness	3.81 μm[150 μin]
Contact Layout	Matrix
Contact Base Material	Copper Alloy
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	.03 μm[1.18 μin]
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Receptacle
Contact Current Rating (Max)	3.6 A

Termination Features

Rectangular Termination Post & Tail Width	.2 mm[.008 in]
Rectangular Termination Post & Tail Thickness	.4 mm[.016 in]
Termination Post & Tail Length	2.54 mm[.1 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

PCB Mount Retention Type	Hold-Down Post
Mating Alignment Type	Polarization
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	Without

Housing Features

Centerline (Pitch)	1.27 mm[.05 in]
Housing Material	LCP

Dimensions

Connector Width	5.03 mm[.198 in]
Connector Height	8.89 mm[.35 in]
Connector Length	7.47 mm[.294 in]
Row-to-Row Spacing	2.54 mm[.1 in]
Stack Height	11.43 mm[.45 in]



PCB Thickness (Recommended)	1.57 mm[.062 in]
-----------------------------	------------------

Usage Conditions

Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Solder Process Feature	Board Standoff
Circuit Application	Signal

Industry Standards

Compatible With Agency/Standards Products	UL
Compatible With Approved Standards Products	CSA LR7189, UL E28476
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	70
Packaging Method	Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on



requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 5-104549-1 10 SYS50 S/M HDR DRST SHRDSN	 TE Part # 5-104068-2 10 SYSTEM 50 HDR DRST SHRD	 TE Part # 6-104666-2 10 SYSTEM 50 HDR DRST SHRD SN	 TE Part # 5-103916-1 10 sys 50 hdr drst unshrd sn
 TE Part # 5-147377-1 10 SYS50 SMT HDR DR SHD SN	 TE Part # 5-104118-3 10 SYS 50 HDR DRRA UNSHRD SN	 TE Part # 6-104477-2 10 SYS50 HDR DRRA 145 SOLDESN	 TE Part # 5-104069-4 10 sys 50 hdr drra shrd sn

Also in the Series | AMPMODU System 50

 Board-to-Board Headers & Receptacles(218)	 PCB Headers & Receptacles(218)	 Rectangular Power Connectors(31)	 Wire-to-Board Headers & Receptacles (31)
---	------------------------------------	--------------------------------------	--

Customers Also Bought

 TE Part #764619-000 CWT-7-W122-5	 TE Part #41729-2 250 FASTON REC 18-16 AWG TPBR	 TE Part #2-1419108-4 RTB14005F	 TE Part #4-1437624-5 PKE90B1/4=KNOB PLASTIC FLUETED
---	---	---------------------------------------	--




TE Part #3-1461491-3
PCN-112D3MHZ,000




TE Part #5-1747072-3
GRACE INERTIA CONN 2.5 ON TAPE
HDR 3P NA



TE Part #1879022-5
SMF3 470R 5%



TE Part #1903392-1
GIC 2.5 W CAP HSG 3P NATURAL



TE Part #M7139-300PG-500000
PRESS XDCR M7139-300PG-500000



TE Part #2041119-2
mSATA/mini PCI-E 4H Type I 10u"

Documents

Product Drawings

10 SYSTEM 50 RCPT ASSY DRST SN

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-104078-3_AA.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5-104078-3_AA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-104078-3_AA.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

AMPMODU_INTERCONNECTION_SYSTEM_SECTION3AND4

English

AMPMODU SYSTEM 50 QUICK REFERENCE GUIDE

English

AMPMODU SYSTEM 50

English

Product Specifications



Application Specification

English

Agency Approvals

Agency Approval Document

English