

TECHNICAL DATASHEET

Doc. No:
TTDS 174 Rev1

Tyco Electronics **EET-...P-4**

EET-...P-4 self-adhesive Thermal transfer printable labels.

Label material	Polyester film, yellow		
Adhesive	Permanent pressure sensitive acrylic		
Liner	Glassine		
Thickness:			
Label	0.05 mm ±10%		ASTM D3652
Adhesive	0.033mm ±10%		ASTM D3652
Liner	0.056mm ±10%		ASTM D3652
Peel Adhesion at 23°C	Stainless steel	700 N/m	FTM 1 (72 hour dwell) Average values
Service Temperature	-40°C to +150 °C		
Minimum application temperature	10 °C		
Print permanence	Dry rub	SAE-AS-81531	
	Print legible after 30 rubs		
Storage stability	2 years at 21°C and 50% RH		
Printability	Thermal transfer		

Tyco Electronics idento GmbH
Paul-Ehrlich-Straße 23
D-63322 Rödermark
Tel.: 06074/8908-0

Tyco Electronics Identto
ZI de Comboire - 1 rue des
Montagnes de Lans
F-38130 Echirolles
Phone: +33 (0) 476 099 696

Author: M Priddle
Print date: 24-Jun-10
Updated: 8-Jun-10
Page: 1 of 1

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Tyco Electronics Corporation makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Tyco Electronics' only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Tyco Electronics Specifications are subject to change without notice. In addition Tyco Electronics reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.