



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Disconnect**

Modular Terminal Block Product Type: **Screw Clamp Terminal Block**

Primary Product Color: **Gray & Orange**

Product Spacing: **6 mm [ .236 in ]**

Number of Positions: **2**

Features

Product Type Features

|                                     |                            |
|-------------------------------------|----------------------------|
| Modular Terminal Block Product Type | Screw Clamp Terminal Block |
|-------------------------------------|----------------------------|

Configuration Features

|                     |            |
|---------------------|------------|
| Number of Levels    | 1          |
| Gauge Type          | A3-B3      |
| Number of Circuits  | 1          |
| Block Function      | Disconnect |
| Number of Positions | 2          |

Electrical Characteristics

|                                                          |        |
|----------------------------------------------------------|--------|
| Operating Voltage Rating (UL & CSA) (Max) - Main Circuit | 150 V  |
| Impulse Withstanding Voltage Rating (IEC)                | 6000 V |
| Current Rating (IEC)                                     | 18 A   |
| Current Rating (UL)                                      | 13 A   |
| Dielectric Withstanding Voltage (Max)                    | 1890 V |
| Voltage Rating (IEC)                                     | 400 V  |



|                                             |       |
|---------------------------------------------|-------|
| Voltage Rating (CSA)                        | 150 V |
| Short-Time Withstanding Current Rating @ 1s | 300 A |

Body Features

|                       |                |
|-----------------------|----------------|
| Product Weight        | 21.6 g[.85 oz] |
| Primary Product Color | Gray & Orange  |

Mechanical Attachment

|                                |                   |
|--------------------------------|-------------------|
| DIN Rail Mounting Type         | TH35-15, TH35-7.5 |
| Terminal Block Disconnect Type | Lever             |
| Connector Mounting Type        | DIN Rail          |

Housing Features

|                  |           |
|------------------|-----------|
| Housing Material | Polyamide |
|------------------|-----------|

Dimensions

|                                                                     |                         |
|---------------------------------------------------------------------|-------------------------|
| Product Depth                                                       | 76.8 mm                 |
| Tool Size                                                           | 3.5 mm[.138 in]         |
| Wire Stripping Length                                               | 10.5 mm[.413 in]        |
| Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp | 24 – 16 AWG             |
| Main Circuit Capacity - Twin Ferrule per Screw Clamp                | 24 – 16 AWG             |
| Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp       | 24 – 16 AWG             |
| Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp  | 24 – 10 AWG             |
| Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp     | .22 – 4 mm <sup>2</sup> |
| Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp         | .22 – 4 mm <sup>2</sup> |
| Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp        | 24 – 10 AWG             |
| Product Length                                                      | 76.8 mm[3.02 in]        |
| Product Height                                                      | 70.5 mm                 |
| Product Spacing                                                     | 6 mm[.236 in]           |

Usage Conditions

|                                |                            |
|--------------------------------|----------------------------|
| Installation Temperature Range | -5 – 40 °C[23 – 104 °F]    |
| Operating Temperature Range    | -55 – 110 °C[-67 – 230 °F] |

Industry Standards

|                        |          |
|------------------------|----------|
| IP Rating              | IP20     |
| UL Flammability Rating | UL 94V-0 |



Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant with Exemptions                                                                                                                                                                                                                                                                                                                                                                                                |
| EU ELV Directive 2000/53/EC                   | Compliant with Exemptions                                                                                                                                                                                                                                                                                                                                                                                                |
| China RoHS 2 Directive MIIT Order No 32, 2016 | 有害物质含量超出标准 Restricted Substance(s) Above Threshold                                                                                                                                                                                                                                                                                                                                                                       |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2025 (250)<br>Candidate List Declared Against: JUNE 2025 (250)<br>SVHC > Threshold:<br>Pb (3.5% in 74024578)<br><b>Article Safe Usage Statements:</b><br>Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content                               | Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                                                                                                                                                                                                                                                                                                                         |
| Solder Process Capability                     | Not reviewed for solder process capability                                                                                                                                                                                                                                                                                                                                                                               |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 1SNA164800R0300  
PR3.G2

TE Part # 1SNA168700R2200  
PR5

TE Part # 1SNK900205R0000  
TP4

TE Part # 1SNK906302R0000  
JB6-2



TE Part # 1SNK906304R0000  
[JB6-4](#)




TE Part # 1SNK900603R0000  
[JB85-3](#)



TE Part # 1SNK900611R0000  
[UMH](#)



TE Part # 1SNK900002R0000  
[BAZ1](#)



TE Part # 1SNA173220R0500  
[PR30](#)




TE Part # 1SNK906303R0000  
[JB6-3](#)




TE Part # 1SNK900612R0000  
[PROCAP6](#)



TE Part # 1SNK900001R0000  
[BAM4](#)




TE Part # 1SNA168500R1200  
[PR4](#)



TE Part # 1SNK150000R0000  
[MC612](#)




TE Part # 1SNK900203R0000  
[TP2](#)



TE Part # 1SNA174300R1700  
[PR3.Z2](#)



TE Part # 1SNK159999R0000  
[MC612PA](#)



TE Part # 1SNK150004R0000  
[MC612-YL](#)



TE Part # 1SNK900105R0000  
[ES-TC6](#)



TE Part # 1SNK906305R0000  
[JB6-5](#)

Also in the Series | **ENTRELEC SNK**



[Modular Terminal Blocks\(319\)](#)



[Terminal Block & Strip Conducting Accessories\(67\)](#)



[Terminal Block & Strip Insulating Accessories\(31\)](#)

Customers Also Bought



Documents

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_1SNK506414R0000\_A.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_1SNK506414R0000\_A.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1SNK506414R0000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ENTRELEC Terminal Block - Master Catalog

ENTRELEC Terminal Block - Master Catalog

English

ZS4-S-R2

English

SNK SERIES TERMINAL BLOCKS

English

ENTRELEC Terminal Blocks Catalogue (RUS)