



RJ45-ECS

Ethernet Connector System

ETHERNET CONNECTOR SYSTEM

The patented RJ45-ECS Ethernet connector system, available exclusively from TE Connectivity, is a field replaceable outdoor rated and shielded Ethernet connection system for high speed 10BaseT, 100BaseT and 1000BaseT networks. The system features a shielded RJ45 receptacle mounted in a UV protected housing and a mating cable gland which passes an RJ45 connector and seals the cable to IP67 requirements. The system provides for quick and easy disconnect and reconnect of equipment.

Because of its many unique design features and low cost, the RJ45-ECS is a universal solution for many industries where a sealed and waterproof, yet removable, Ethernet connection is required. These include outdoor applications such as wireless equipment or video surveillance equipment, and indoor applications such as equipment used in factory automation or harsh industrial processes. RJ45 connectors are not designed for high reliability in the presence of moisture, dust, or corrosive elements. For this reason, the IP67 sealing ability of the RJ45-ECS provides a reliable connection, even in very harsh environments, for many years of trouble free service. The shielded nature of the Cat5e cable and connectors provide maximum shielding against external EMI for consistent data communications. For modern wireless systems, the quick disconnect feature allows for ready replacement of rooftop equipment, to minimize field time spent servicing customer's equipment, and minimizing downtime for the customer. This helps to increase operator profitability and customer satisfaction.

FEATURES

- Patented low cost design
- Field replaceable waterproof connector system for RJ45 shielded or unshielded connectors
- Constructed of UV protective materials for long life in harsh outdoor environments
- Seal meets IP67 criteria
- Shock and vibration resistant
- Positive locking RJ45 connector
- 12 in Cat5E strain relieved cable

MARKETS

- Wireless base stations
- Telecom equipment
- Wireless client radios
- 802.11 a/b/g wireless systems
- Direct burial equipment
- 10BaseT, 100BaseT or 1000BaseT networks
- Industrial process control
- Factory automation
- WiMAX



* No Relief Version Shown Here



SPECIFICATIONS

Data	10BaseT, 100BaseT and 1000BaseT Networks CAT5e per TIA/EIA 568B ClassD per ISO/IEC 11801
Mechanical	Mating Cycles >500 Positive RJ45 bayonet coupling Cat5 Cable Strain Relief
Material	UV Resistant Nylon 66
Sealing	IP67
Salt Spray	>1000 h
Flammability	UL94VO
Thermal Shock	10 cycles -40 to +100°C
Temperature Range	-40°C to +85°C
Installation Hole Dia	0.787 in (20 mm)
Overall Size (L x Dia)	3.75 in x 1.18 in (95 x 30 mm)
Weight	2 oz (57 gm)

SYSTEM ORDERING INFORMATION

RJ45-ECS	12 in RJ45 Waterproof Outdoor Ethernet Connector System
RJ45-ECS-NR	12 in RJ45 Waterproof Outdoor Ethernet Connector System with no relief
RJ45-ECS-4	4 in RJ45 Waterproof Outdoor Ethernet Connector System
RJ45-ECS-4-NR	4 in RJ45 Waterproof Outdoor Ethernet Connector System with no relief
RJ45-ECS-6	6 in RJ45 Waterproof Outdoor Ethernet Connector System
RJ45-ECS-6-NR	6 in RJ45 Waterproof Outdoor Ethernet Connector System with no relief

NOTES

- All shipments F.O.B. Schaumburg, IL 60173

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. Other product names, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, complete, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event will TE be liable for any direct, indirect, incidental, special or consequential damages arising from or related to recipient's use of the information. It is the sole responsibility of recipient of this information to verify the results of this information using their engineering and product environment. Recipient assumes any and all risks associated with the use of the information. Antenna performance may vary. TE is a component manufacturer, and customer and/or end-user is responsible for all end-use compliance and regulatory requirements.

©2025 TE Connectivity. All Rights Reserved.

05/25 Original