154N-300G-RT ✓ ACTIVE

MEAS | MEAS 154

TE Internal #: 154N-300G-RT

TE Internal Description: 300 PSIG RIBBON CABLE TUBE PRESS

SENSOR

19MM MV OUTPUT PRESSURE SENSOR

View on TE.com >



Sensors > Pressure Sensors > Media Isolated Pressure Sensors > 19MM MV OUTPUT PRESSURE SENSOR



Pressure: [300 psi]

Pressure Sensor Type: mV Output Pressure Sensors

Pressure Type: Gauge Output Signal Type: 100mV

Operating Temperature Range: -40 - 125 °C [-40 - 257 °F]

All 19MM MV OUTPUT PRESSURE SENSOR (38)

Features

Product Type Features	
Pressure Sensor Type	mV Output Pressure Sensors
Pressure Type	Gauge
Sensor Package	O-Ring Mount
Configuration Features	
Electrical Connection	Ribbon Cable
Electrical Characteristics	
Supply Current	1.5 mA
Dimensions	
Product Diameter	18.97 mm[.746 in]
Product Height	13.8 mm[.54 in]
Usage Conditions	
	300 psi
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Operation/Application	

3X

Proof Pressure Range



Output Signal Type	100mV	
Other		
Non-Linearity ±	.1 %	

Vent Tube

Product Compliance

Sensor Options

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Tetraglyme (2% in Component Part) Methanone, (diphenylphosphinyl)(2,4,6-trimethylphenyl)- (1% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | MEAS 154



Customers Also Bought









TE Part #30F-HND-005S-0000A 5PSI, CLOSED BRIDGE, STD PADS

TE Part #5108E-030-A SM68E, 30PSI, 400UM THICK DIE

Documents

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_154N-300G-RT_F1.2d_dxf.zip

English



Customer View Model

ENG_CVM_CVM_154N-300G-RT_F1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_154N-300G-RT_F1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

154NC

English