




Wire Protection & Management > Wiring Ducts & Accessories > Wiring Ducts & Covers > PVC Wiring Duct: 2 meters, Gray Color, Flame-Retardant



Wiring Duct Product Type: **Wiring Duct**

Primary Product Material: **PVC**

Product Height: **100 mm [3.937 in]**

Product Length: **2000 mm [78.74 in]**

Product Width: **25 mm [.984 in]**

[All PVC Wiring Duct: 2 meters, Gray Color, Flame-Retardant \(23\)](#)

Features

Product Type Features

Wiring Duct Product Type	Wiring Duct
--------------------------	-------------

Body Features

Primary Product Color	Gray
Primary Product Material	PVC

Dimensions

Product Height	100 mm[3.937 in]
Product Length	2000 mm[78.74 in]
Product Width	25 mm[.984 in]

Usage Conditions

Operating Temperature Range	-5 – 60 °C[23 – 140 °F]
-----------------------------	-------------------------

Packaging Features

Packaging Quantity	22
--------------------	----



Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1SET411201R0000
WD-1-CP-GR025



TE Part # 1SET411401R0000
WD-1-TL-0001



TE Part # 1SET411407R0000
WD-1-TL-0007



TE Part # 1SET411402R0000
WD-1-TL-0002

Customers Also Bought

1SET411007R0000

Wiring Duct, PVC, 100 mm [3.937 in] Height, 2000 mm [78.74 in] Length, 25 mm [.984 in] Width, -5 – 60 °C [23 – 140 °F]



TE Part #CAT-Z62-W1-DP
PVC Wiring Duct: 2 meters, Gray
Color, Flame-Retardant

TE Part #1SNA400817R0000
MA2.5/5-2CPE

TE Part #1SNA400825R0000
FEDCP

TE Part #1SNA168410R0700
RTM7

TE Part #1SNA400813R0000
MA2.5/5.D2-2CPE

TE Part #1SSA265202R1100
L26520211000

Documents

Product Drawings

WD-1-DP-GR2510

French

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SET411007R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SET411007R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SET411007R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Infographic - entrelec ews-linecard

English

Datasheet - ENTRELEC-wiring-duct-DS

English

Datasheet - Entrelec Electrical-Solutions

Essential Entrelec Terminal Blocks

French

Essential Entrelec Terminal Blocks

1SET411007R0000

Wiring Duct, PVC, 100 mm [3.937 in] Height, 2000 mm [78.74 in] Length, 25 mm [.984 in] Width, -5 – 60 °C [23 – 140 °F]



English

[Essential Entrelec Terminal Blocks](#)

Japanese

[Agency Approvals](#)

[Agency Approval Document](#)

English