TE Internal #: 2195873-1

Flexible PCB (FPC) Antenna, Multi Band, Cellular / GNSS / LTE,

External Mount, Connector Mount, Omnidirectional, Single Port, 3

< 6 dBi Peak Gain

View on TE.com >



Antennas



Communication Protocol: Cellular, GNSS, LTE

Mounting Location: External

Mounting Type: Connector Mount
Frequency Category: 698 – 2700
Antenna Type: Flexible PCB (FPC)

Features

Product Type Features

Antenna Product Type	Antenna
Configuration Features	
Antenna Style	Flexible PCB
Mounting Location	External
Antenna Type	Flexible PCB (FPC)
Band Type	Multi Band
Port Configuration	Single Port
Electrical Characteristics	
Impedance	50 Ω
Antenna Operation	Passive
VSWR (Max)	<4.0:1
Signal Characteristics	
Frequency Category	698 – 2700

3 < 6 dBi

Peak Gain



Body Features

Product Weight	44 g[1.58 oz]
Mechanical Attachment	
Polarization	Linear
Mounting Type	Connector Mount
Dimensions	
Product Width	46.95 mm[1.85 in]
Product Length	61.9 mm[2.44 in]
Product Height	16.1 mm[.634 in]
Cable Length	.2 m[.66 ft]
Operation/Application	
Wireless Standard	Cellular, GPS
Directionality	Omnidirectional
Industry Standards	
Communication Protocol	Cellular, GNSS, LTE
Primary Application	Cellular, GNSS, LTE
Product Availability	
Applicable Region	Americas
Packaging Features	

Product Compliance

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Box



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









Documents

Product Drawings

LEMBAS LTE GNSS USB Modem

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2195873-1_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2195873-1_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2195873-1_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

Instructions Manual LEMBAS

English

Flexible PCB (FPC) Antenna, Multi Band, Cellular / GNSS / LTE, External Mount, Connector Mount, Omnidirectional, Single Port, 3 < 6 dBi Peak Gain



Product Specifications

Product Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English